

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1069-70)

-----  
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 23, 24, 25, & 26, with brass cap mkd:

T21S R10W  
S 23|S 24  
S 26|S 25  
1919

from which

- A Maple, 8" dia., bears N.21°E., 45 lks., mkd: T21S R10W S24 BT.
- A Fir, 20" dia., bears S.82°E., 29 lks., mkd: T21S R10W S25 BT.
- A Fir, 22" dia., bears S.38°W., 4 lks., mkd: T21S R10W S26 BT.
- A Fir, 20" dia., bears N.78°W., 10 lks., mkd: T21S R10W S23 BT.