

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1075-6)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 13, 14, 23, & 24, with brass cap mkd:

T21S R10W
S 14|S 13
S 23|S 24
1919

from which

- An Alder, 16" dia., bears N.31°E., 30 lks., mkd: T21S R10W S13 BT.
- An Alder, 10" dia., bears S.85°E., 70 lks., mkd: T21S R10W S24 BT.
- An Alder, 18" dia., bears S.55°W., 38 lks., mkd: T21S R10W S23 BT.
- An Alder, 16" dia., bears N.80°W., 47 lks., mkd: T21S R10W S14 BT.