

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1078)

-----  
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 11, 12, 13, & 14, with brass cap mkd:

T21S R10W  
S 11|S 12  
S 14|S 13  
1919

from which

- A Chittem, 10" dia., bears N.76°E., 36 lks., mkd: T21S R10W S12 BT.
- A Cedar, 40" dia., bears S.30°E., 80 lks., mkd: T21S R10W S13 BT.
- A Vine Maple, 6" dia., bears S.80°W., 124 lks., mkd: T21S R10W S14 BT.
- A Chittem, 14" dia., bears N.70°W., 57 lks., mkd: T21S R10W S11 BT.