

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 641700

PRIMARY CORNER DESCRIPTION S. 1/4 Cor. for Sec. 36 only, T20-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 210)

Set post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face; from which an
Alder 12" dia., bears S.24°W., 8 lks. dist. mkd. ¼ S BT.
Alder 12" dia., bears N.34°W., 10 lks. dist. mkd. ¼ S BT

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (Group #36) (surveyed 1919) - (DCSO records Vol. 1 Page(s) 260) and (Dup. Pg. 1065)

Intersect the old ¼ sec. cor., which is a badly decayed post, marked and witnessed as described by the surveyor general. I obliterate marks on the bearing tree referring to sec. 1 and change this cor. to refer to sec. 35 only and alongside the old cor., SET an iron post 3 ft. long, 1" dia., 26" in the ground, for ¼ sec. cor., of sec. 36 only, with brass cap marked: ¼ S 36

1919
from which
A Wild Cherry 10" dia., bears N.26°E., 38 lks. dist. mkd. ¼ S36 BT. (New BT)
An Alder 12" dia., bears N.30°W., 10 lks. dist. mkd. ¼ S36 BT. (Old BT)

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11664-65)

The ¼ sec. cor., monumented with an iron post 1" dia., 8" above ground, firmly set, with brass cap mkd. in 1918. There is no trace of the old bearing trees.
The old iron post is rusted nearly through; in its place Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap mkd. ¼ S 36

1951
from which
A Cedar 40" dia., bears N.57¼°E., 94 lks. dist. mkd. ¼ S36 BT.
A Hemlock 36" dia., bears N.30°W., 32 lks. dist. mkd. ¼ S36 BT.
Deposit the old iron post at the base of the new iron post.

Fd. OK, Oct. 1984 by R. Stuntzner - M 97-80

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 641700

PRIMARY CORNER DESCRIPTION S. 1/4 Cor. for Sec. 36 only, T20-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Jerry Estabrook - For: Roseburg Resources - 1/2022 - M180-48

-
- Found - A 1" iron pipe with 2½" brass cap (properly)marked.
Set steel post alongside
- A 40" Cedar snag with open face and no visible marks
bears N.57°15'E., 62.04'.
- A rotten 36" Hemlock stump with no visible marks
bears N.30°W., 21.12'.
- New BTs- A 22" Fir, face scribed "X BT" with X- chop and tag
bears S.40°E., 8.8' to a spike at side center.
- An 18" Fir, face scribed "X BT" with X- chop and tag
bears S.53°W., 20.1' to a spike at side center.
- A 13" Fir, face scribed "X BT" with X- chop and tag
bears S.85°W., 19.2' to a spike at side center
- A 1" iron pipe with 2½" brass cap marked "¼ S1 1951"
bears S.89°22'07"W., 75.47'.

Lat and Long per GARMIN ETREX hand held GPS:
N: 43°46'57.2" W: 123°50'19.3"