

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Charles Collier, and Fred Rodolf, U.S. Cadastral Engineers; Elmr Strickler, U.S. Surveyor and Gerald Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1037)

 Intersect the point for closing cor. of Tps. 21 S., R 10 W. and 22 S., R9W, located by reference to the old bearing trees. At the exact cor. point, Set a hard sandstone, 16x10x8 ins., 11" in the ground, for closing cor. of T21S R10W and T22S R9W, marked C C on E., with 6 grooves on E. and S. faces, from which
 An Alder 12" dia., bears N.71°E., 27 lks. dist. mkd. T21S R10W S36 BT. (Old BT)
 An Alder 10" dia., bears S.29°E., 28 lks. dist. mkd. T21S R10W S6 BT. (Old BT)

BLM resurvey by Harvey Wofford; Wayne Rogers and Owen Chatters II, Cadastral Surveyors under Group #'s 811 and 1000 - surveyed Aug. 1973/Oct. 1979 - (DCSO records Vol. 40 Page(s) 16028)

 The closing cor. of T21S R10W, and T22S R9W, monumented with an unmarked sandstone, 16x10x8", firmly set in a mound of stone, 3 ft. base, 1 ft. high.
 At the corner point
 Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap
 mkd:
 T 21 S
 T 22 S R 10 W
 R 10 W S 36 C
 S 1 S 6 C
 T 22 S
 R 9 W
 1974
 from which
 A Cedar 22" dia., bears N.32°E., 23 lks. dist. mkd. T21S R10W S36 CC BT.
 A Hemlock 13" dia., bears S.42°E., 87 lks. dist. mkd. T22S R9W S6 CC BT.
 Deposit corner stone alongside iron post.

Closing corner Fd. OK by Malloy and Farnsworth in BLM resurvey, under Group #'s 1125 and 1226, surveyed Nov/Dec. 1982 - (DCSO records Vol. 47 Page(s) 17936)