

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30 only, T21-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 2 Page(s) 904-05)

Set sandstone 12x10x8 ins., 9" in the ground on steep hill side sloping W. for cor. to secs. 19, 30, 24 and 25, marked with 2 notches on the S. and 4 notches on the N. edges, from which

- A Fir 12" dia., bears N.26°30'E., 57 lks. dist. mkd. T21S R9W S19 BT.
- An Alder 8" dia., bears S.34°45'E., 14 lks. dist. mkd. T21S R9W S30 BT.
- A Fir 26" dia., bears S.44°45'W., 27 lks. dist. mkd. T21S R10W S25 BT.
- A Fir 24" dia., bears N.49°45'W., 72 lks. dist. mkd. T21S R10W S24 BT.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 990-91) and Dup. Pg.1026)

Intersect the old cor. of secs. 19, 24, 25 and 30, which is a sandstone, marked and witnessed as described by the surveyor general. I obliterate marks on SW. and NW. bearing trees and change this cor. to refer to secs. 19 & 30 only and alongside the old cor., Set an iron post, 3 ft. long, 2" dia., 24" in the ground, with brass cap mkd.

T 21S
S 19
S 30
R 9 W
1919

from which

- A Fir 18" dia., bears N.30°E., 60 lks. dist. mkd. T21S R9W S19 BT. (Old BT)
- An Alder 12" dia., bears S.46°E., 15 lks. dist. mkd. T21S R9W S30 BT. (Old BT)

Corner report by V. Wylie Smith III - For: BLM - Dec. 30, 1971 - C.S. File 55/230

Corner obliterated by slide from the newly constructed road. Found Orig. BT, 1894 survey by Gesner who re-established sec. cor. from this BT:

- 34" Fir bears N.49°45'W., for 72 lks. to face of tree. Find axe marks & a grown over face.

(Cont. Next Page)

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 700254

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30 only, T21-9

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

Set 1/2" x 18" reinforcing rod 8" into solid sandstone on West facing slope.

Marked:

30" Fir bears N.45°00'W. for 84 ft. to centerline. Tree faced and scribed "Sec.Cor."

36" Fir bears N.9°00'E. for 62 ft. to centerline tree. Tree faced and scribed "Sec. 19 Cor."

Tony Hostetter - For: Roseburg Resources - Jan. 2020 - C.S. File 65/105-8

Found - 1/2" iron rod in sandstone as set by Smith in 1971 (C.S. File 55/230A) from which:

40" Fir, face evident, BT tag bears; N.09°32'E., 69.7 FT to center. (Record: N.9°E., 62.0 FT to center).

38" Fir, face evident, BT tag, bears; N.45°05'W., 84.0 ft to center. (Record: N.45°W., 84.0 ft to center).

40" Fir, face evident, BT tag, bears (rec N.49°45'W. 47.5 ft to face).