

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 700314

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 19 only, T21-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 2 Page(s) 905)

Set Alder post 4 ft. long, 4" sq., 24" in ground for ¼ sec. cor. mkd. ¼ S on the W. face, from which

An Alder 10" dia., bears N.87°E., 14 lks. dist. mkd. ¼ S BT.

A Fir 25" dia., bears S.63°W., 30 lks. dist. mkd. ¼ S BT

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 992) and (Dup. Pg. 1027)

Intersect the point for old ¼ sec. cor., located by reference to the bearing trees. I obliterate marks on the bearing tree referring to sec. 24 and change this cor. to refer to sec. 19 only. At the exact cor. point, Set an iron post 3 ft. long, 1" dia., 26" in the ground for ¼ sec. cor. sec. 19 only, with brass cap mkd. ¼

S 19
1919

from which

An Alder 14" dia., bears N.66°E., 16 lks. dist., mkd. ¼ S19 BT. (Old BT)

A Fir 36" dia., bears S.36°E., 38 lks. dist. mkd. ¼ S19 BT. (New BT)