

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19 only, T21-9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 2 Page(s) 906)

A sandstone in place, 40 x 24 x 10 ins., above ground on steep hill side, sloping South, marked it with 3 notches on the N. and S. sides, with X on top at front, for cor. to secs. 18, 19, 13 and 24, from which

- A Fir 36" dia., bears N.14°E., 65 lks. dist. mkd. T21S R9W S18 BT.
- A Fir 30" dia., bears S.61°30'E., 34 lks. dist. mkd. T21S R9W S19 BT.
- A Fir 20" dia., bears S.60°W., 41 lks. dist. mkd. T21S R10W S24 BT.
- A Fir 26" dia., bears N.67°15'W., 66 lks. dist. mkd. T21S R10W S13 BT.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 993) and (Dup. Pg. 1028-29)

Intersect the old cor. of secs. 13, 18, 19 and 24, which is a sandstone, firmly set, marked and witnessed as described by the surveyor general, except the NE. bearing tree has fallen. I obliterate marks on SW. and NW. bearing trees and change this cor. to refer to secs. 18 & 19 only, and alongside the old cor., Set an iron post 3 ft. long, 2" dia., 24" in the ground, with brass cap mkd:

T21S
S 18
S 19
R9W
1919

- from which
- A Fir 30" dia., bears N.84°E., 68 lks. dist. mkd. T21S R9W S18 BT. (New BT)
 - A Fir 36" dia., bears S.62°E., 36 lks. dist. mkd. T21S R9W S19 BT. (Old BT)