

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 700509

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 7 only, T21-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 2 Page(s) 908)

-----  
Set sandstone 12x8x6 ins., 9" in the ground on steep hill side, sloping S., for ¼ sec. cor., marked ¼ S on the W. face, from which  
A Fir 24" dia., bears S.21°W., 175 lks. dist. mkd. ¼ S BT  
A D.Fir 16" dia., bears S.43°E., 21 lks. dist. mkd. ¼ S BT

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 996-97) and (Dup. Pg. 1032)

-----  
Intersect the old ¼ sec. cor., which is a stone, firmly set, marked and witnessed as described by the surveyor general. The old SE. bearing tree is dead. I obliterate marks on the old SW. bearing tree and change this cor. to refer to sec. 7 only and alongside the old cor., Set and iron post 3 ft. long, 1" dia., 26" in the ground, for ¼ sec. cor., with brass cap mkd: ¼

S 7  
1919

from which  
A Fir 9" dia., bears N.86°E., 13 lks. dist. mkd. ¼ S7 BT  
A Fir 12" dia., bears S.75°E., 21 lks. dist. mkd. ¼ S7 BT