

PRIMARY CORNER DESCRIPTION A P on E. bdy. Sec. 12

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 2 Page(s) 908-09)

Set Fir post 5 ft. long, 5" sq., 24" in the ground on steep hill side sloping SE. for cor. to secs. 6, 7, 1 and 12, marked T21S S6 on the NE.; R9W S7 on the SE.; R10W S12 on the SW.; and S1 on the NW. faces, with 5 notches on the S. and 1 notch on the N. edges, from which

A Fir 60" dia., bears N.69°45'E., 70 lks. dist. mkd. T21S R9W S6 BT.

An Alder 14" dia., bears S.53°30'E, 38 lks. dist. mkd. T21S R9W S7 BT.

A Maple 7" dia., bears S.11°15'W., 19 lks. dist. mkd. T21S R10W S12 BT.

A Fir 4" dia, bears N.67°15'W., 25 lks. dist. mkd. T21S R10W S1 BT.

(This corner sets just above a large Fir log, lying along the hill side nearly E. and W.)

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 997-98) and (Dup. Pg.1033)

Intersect the point for old cor. of secs. 1, 6, 7 and 12, located by reference to the old NW. bearing tree. At the exact cor. point, Set an iron post 3 ft. long, 1" dia., 26" in the ground, for Angle Point, with brass cap mkd:

>AP
1919

from which

A Fir 12" dia., bears N.20°E., 34 lks. dist. mkd. AP BT.
(New BT)

A Fir 14" dia., bears N.63°W., 24 lks. dist. mkd. AP BT.
(Old BT)

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14215-16)

The angle point bet. secs. 7 & 12, on the E. bdy. of T21S R10W., determined at record bearing and distance from the bearing trees marked by Collier and Rodolf in 1919:

A Fir 20" dia., bears N.20°E., 34 lks. dist., with healed blaze.

(Cont. Next Page)

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 700548

PRIMARY CORNER DESCRIPTION A P on E. bdy. Sec. 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 30" dia., bears N.63°W., 24 lks. dist., with healed blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd: >AP
1966