

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 700568

PRIMARY CORNER DESCRIPTION CC for Secs. 6 & 7 only, T21-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 3 Page(s) 982-83)

Set closing cor. to secs. 6 & 7, which is an Alder post 4½ ft. long, 5" sq., 24" in the ground mkd. S6 on the N.; T21S R9W on the E.; S7 on the W.; and CC on the N. faces, with 5 grooves on the S. and 1 on N. edges, from which

A Fir 24" dia., bears N.37°E., 108 lks. dist. mkd. T21S R9W S6 BT.

A Fir 24" dia., bears S.55°E., 153 lks. dist. mkd. T21S R9W S7 BT.

A Cedar 24" dia., bears N.86°30'W., 92 lks. dist. mkd. CC T21S R9W S6 & 7 BT.

GL0 resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 998) and (Dup. Pg. 1033-34)

Intersect the point for old closing cor. of secs. 6 & 7, located by reference to the old bearing trees, which are as described by the surveyor general. At the exact cor. point, Set an iron post, 3 ft. long, 2" dia., 24" in the ground for closing cor. of secs. 6 & 7, with brass cap mkd:

| T21S
| S 6
| S 7 — CC
| R9W
1919

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14216)

The closing cor., monumented with an iron post, 2" dia., extending 16 above ground, firmly set, with brass cap mkd. in 1918,

from which the original bearing trees:

A Fir 65" dia., bears N.37°E., 108 lks. dist., with healed blaze.

A Fir 67" dia., bears S.52°E., 153 lks. dist., with healed blaze. (Rec. S.55°E.)

and new bearing trees:

A Fir 20" dia., bears N.83½°E., 46 lks. dist. mkd. T21S R9W S6 CC BT.

(Cont. Next Page)

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 700568

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only, T21-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Cedar 6" dia., bears S.86°E., 78 lks. dist. mkd. T21S R9W S7 CC BT.
This corner became a fixed point and angle point in the line in 1919.

Douglas Co. Surveyors Office - Larry Monrean, Deputy - J.M. Powell; R.L. Smith, crew - Jan. 25, 1982 - C.S. File 61/30-12

Found - A 1 3/4" Iron pipe, firmly set, filled with concrete and rusted off 4" above ground. Upper portion of pipe with a GL0 1918 properly mkd. brass cap, has been placed alongside lower portion.
Orig. Fir, 65", now a 69" dia. stump with well healed blaze, bears N.35½°E., 69.4 ft. (Rec. N.37°E., 71.3 ft.)
Orig. Fir, 67" dia., now a stump with visible burl, bears S.52°E., 118.7 ft. (Rec. 101.0 ft.)
1966 Resurvey, a Fir 20", now a 24" dia. stump with well healed blaze, bears N.85°E., 27.8 ft.
1966 Resurvey, a Cedar 6", now a 10" dia. stump with unhealed blaze, scribed "T21S R9W S7 CC BT", bears S.86°E., 48.1 ft. (Rec. 51.5 ft.)
Set a 1" x 30" Galv. I.P. with brass cap attached at position of found monument along northerly side. Cap stamped: "Douglas County Surveyor T21S R10W CC S6 S7 R9W 1982".
As there are no trees available to scribe, WE SET:
A railroad spike in the pitch ring of a 24" dia. Fir stump. Spike is stamped "B0" and bears S.55½°E., 53.6 ft.
Cor. lies on S. side of a spur ridge sloping westerly.
(Sketch in file)

Jerry Estabrook - For: Roseburg Resources - 1/2022 - M180-48

Found - A 1" iron pipe with 2½" brass cap (properly) marked 1¾" iron pipe alongside.
A 69" Fir stump with healed face and tag bears N.35°'30'E., 69.4'.
A 24" Fir stump with visible scribe in face bears N.85°E., 27.8'.
A 10" Cedar stump with healed face and tag bears S.86°E., 48.1'.
A 67" rotten fir stump with no visible marks bears S.52°E., 118.7'.
A Railroad spike stamped "B0" in 24" fir stump bears S.55°30'E., 53.6'.

Continued next page

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 700568

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only, T21-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- A 12" Fir, face scribed "X BT" with X-chop and tag
bears S.23°W., 4.5' to a spike at side center
A 16" Fir, face scribed "SW S6 BT" with X-chop and
tag bears N.25°E. 11.0' to a spike at side center
New B0 - A steel post bears West 1.5'.
Lat and Long per GARMIN ETREX hand held GPS.
N: 43°46'01.5" W: 123°49'28.4"