

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION W.C. to NE Cor. Sec. 1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 2 Page(s) 910-11)

Intersected the left bank of Smiths River, as the post for Cor. will come in the river, I set chittewood post 5 ft. long, 4½" sq., 24" dia., in the ground for witness closing cor. to T21S Rgs. 9 & 10 W. marked WCC T21S on the S.; R9W S6 on the E.; and R10W S1 on the W. faces, with 6 grooves on the S., E., and W. faces, from which
A Cedar 40" dia., bears S.42°E., 70 lks. dist. mkd. T21S R9W S6 BT.
A Maple 12" dia., bears S.89°W., 97 lks. dist. mkd. T21S R10W S6 BT.
A Cedar 45" dia., bears N.38°W., 33 lks. dist. mkd. W CC T21S R9 & 10 W S6 BT.

GL0 resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1000) and (Dup. Pg. 1035)

72.70 chs.)
Intersect point for the witness cor. to the closing cor. of Tps. 21S., Rs. 9 and 10 W., located by reference to the old bearing trees. At the exact cor. point, SET an iron post 3 ft. long, 3" dia., 24" in the ground, for witness cor. to the clsoing cor., with brass cap mkd:
T20SR9W
CC
S1 | S6
R10W | R9W
WC
T21S
1919

from which
A Cedar 40" dia., bears S.42°E., 70 lks. dist., mkd. WC CC T21S R9W S6 BT.
A Maple 12" dia., beras S.89°W., 97 lks. dist. mkd. WCCC T21S R10W S1 BT.
(73.95 chs.)
The point for closing cor. of Tps. 21S Rs. 9 & 10 W. falls in Smith River.

(Cont. Next Page)

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION W.C. to NE Cor. Sec. 1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - P. Earle and D. Stewart - Nov. 5, 1975 - C.S. File 57/39-4

Found - A Cedar 40" now 52" dia., bears S.42°E., 44.5 ft. (Rec. 46.2 ft.) blazed.
A Cedar 45" now 55" dia., bears N.38°W., 21.8 ft. scribed "WCC T21S R9 & 10 W."
Maple BT not found, bearing distance recorded falls in large growth of Maples in slide area.

Set brass cap at witness cor. to closing cor. stamped:
County Surveyors Office 1975

T 20 S R 9 W
- CC
S 1 | S 6
R10W | R9W

Corner lies near South bank of Smith River, nearly directly across river from fence running N. & S. at East end of Fawn Creek Park.

Jerry Estabrook - For: Roseburg Resources - 1/2022 - M180-48

Found WC- A 1" iron pipe with 2½" brass cap (properly) mkd
A 65" Cedar with healed face bears S.42°E., 44.5' placed new tag on BT.
A 55" Cedar stump with no visible marks bears N.38°W., 21 8'.
A steel post bears N.10°E., 1.2'.
New - A steel post bears South 3.0'.
A steel post bears West 3.0'.
Lat and Long per GARMIN ETREX hand held GPS:
N: 43°46'57.0" W: 123°49'28.7"