

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T21-12

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1151)

Set post cor. of secs. 13, 18, 19 and 24, from which
A Hemlock 10" dia., bears S.83°E., 47 lks. dist.
A Spruce 36" dia., bears N.62°E., 42 lks. dist.
A Hemlock 8" dia., bears N.86°W., 77 lks. dist.
A Vine Maple 5" dia., bears S.45°W., 16 lks. dist.

F.C. Frear - Wit: N.E. Richardson; James Wolford - C.S. File 16/55 - Oct. 20, 1940 (I question this date?)

Drove 2" x 5 ft. pipe for corner, from which
7" Fir bears S.70 3/4°E., 7.4 ft.
12" Fir bears S.12½°E., 8.3 ft.
8" Fir bears N.79½°W., 18.2 ft.
10" Fir bears N.44°E., 21.8 ft.

Frank Cain - Harry Henderson, H.L. Eppstein - Jan. 25, 1929 -C.S. File 16/55 (I question this date?)

There was an Iron pipe 2" x 5 ft. driven in ground for this corner by previous surveyor, the old bearing trees gone but remains of stump check with field notes, but burned so bad, no scribe marks visible. Did not mark new tree on account of being too far off.

Survey by Harry Hugill - For: Walter Pyritz - Jan. 15, 1949 -C.S. File 40/169

At sec. cor., which point I found to be marked by an I.P. with bearing trees as called for plainly evident.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy and crew - Nov. 25, 1964 - C.S. File 53/66-56

Found - 2" Iron pipe mentioned by Frank Cain. Pipe extends approx. 12" above ground.
No trace of any original bearing trees.
New BTs -16" D.Fir S.8°W., 8.4 ft. mkd. T21S R12W S24 CS BT.
14" D.Fir S.60°E., 24.7 ft. mkd. T21S R11W S19 CSBT
13" D.Fir N.77°E., 27.2 ft. mkd. T21S R11W S18 CSBT
No suitable trees near in section 13.
DID NOT SET BRASS CAP.
Corner is approx. 500 ft. W. of Smith River Road.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. cor. for 18 & 19, 13 & 24, T21-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - James Byron, Co. Surveyor -
John M. Powell and crew - April 1, 1970 - C.S. File 54/110

Found - 2" Iron pipe at corner, 12" above ground.
16" now 16" D.Fir S.8°W., 8.4 ft., shows pitched
over scribing.
14" now 14" D.Fir S.60°E., 24.7 ft., shows pitched
over scribing.
13" now 13" D.Fir N.77°E., 27.2 ft., shows pitched
over scribing.
New BT - 12" Hemlock N.67°W., 26.4 ft. scribed T21S R12W S13
CS BT.

Douglas County Surveyors Office - L.E. Monrean, Deputy - K.
Reed; P. Earle; S. Flause; F. Silagy, crew - Nov. 15, 1978 -
C.S. File 60/17-25

Found - An I.P. 2" dia., 17" high set by Frear in 1940.
A 7" now 8" Fir, is tipped out, bears S.70 3/4°E.,
7.4 ft. Tree partially rotted. scribing visible
"19 BT".
An 8" Fir now a 10 ft. high stump bears N.49½°W.,
18.2 ft. Tree partially rotted, has healed over
blaze.
A Fir 10" now 12", bears N.44°E., 21.8 ft. Has
healed blaze.
A 16" now 21" D.Fir, bears S.8°W., 8.4 ft. Has well
healed blaze.
A 14" now 18" D.Fir, bears S.60°E., 24.7 ft. Has
well healed blaze.
A 13" now 18" D.Fir bears N.72½°E., (Rec. N.77°E.)
26.6 ft. (Rec. 27.2 ft.)
A 12" now 14" Hemlock bears N.67°W., 26.4 ft. Tree
has partially healed blaze.
No new monument or accessories set.

Survey by Robert Ward, Jr. - For: International Paper Co. -
Jan. 6, 1988 - M 105-64

Found - 2" Iron pipe extending 16" out of ground.
16" Hemlock bears N.68°W., 27.0 ft. with healed face
24" Fir bears S.6½°W., 8.4 ft. with healed face.
20" Fir stump bears S.62 3/4°E., 24.6 ft. with
healed face.
20" Fir stump N.72½°E., 26.8 ft. with healed face.
Replaced 2" iron pipe with 3/4" alum. cap mkd. LS 1091.

(Cont. Next Page)

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T21-12

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Clyde F. Mulkins, for I.P. Timberlands, Jan 18 1994, M118-62

Found - 3¼" Alum cap with 3/4" x 30" Alum rod
19" Hemlock with a healed face, bears N.68°W., 27'
20" DF stump with a healed face, bears N.72½°E.,
26.8 ft.
27" DF with a healed face, bears S.6½°W., 8.4'
New BT - 7" W. Fir I scribe "S13 T21S R12W BT", bears N.1°W.,
35 ft.

Fd. Ok - Clyde Mulkins - Mar. 1995 - 1996-0014 A&B
Fd. OK - Clyde Mulkins - Sep. 1996 - M 124-16.
Fd. OK - Troy Rambo - May 2010 - M160-70