

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1231)

Set a post 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor. marked ¼ S BT, from which

A Cherry 3" dia., bears N.48°E., 8 lks. dist. mkd. ¼ S BT.

An Alder 6" dia., bears S.7°E., 14 lks. dist. mkd. ¼ S BT.

Survey by Richard J. Hintz - For: International Paper Co. - Sept. 1976 - M 62-1

Set 5/8" Iron rod, from which

A 28" W.Fir bears West, 32.7 ft., scribed.

A 16" Hemlock bears S.50°E., 22.3 ft., scribed.

(This cor. not proper 1/4 corner - See M 70-74 - corner left in field.) (Per M 88-52, 1/4 Cor. was removed and not reset)

Survey by Les Roberts, LS #1039 - For: International Paper Co. - Nov. 27, 1990 - C.S. File 63/126-23 and M 111-9

Set 3/4" x 36" alum. rod with 3¼" alum. cap by single proportionate measure. Buried purple magnetic marker under alum. rod. Set 60" alum. post with land monument sign beside alum. rod.

New BTs -27" Fir stump S.31°E., 32.4 ft. RR spike/painted red.

35" Hemlock stump N.85°W., 5.3 ft. RR spike/painted red.

Corner lies on steep North slope about 25 ft. North of ridge. Ridge bears NW. and SE.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 4/18/2002 - C.S. File 66/32-32

Found - 1990 3/4" alum. rod with 3¼" dia., alum. cap protrudes 4" out of ground.

Two stumps as previously recorded with boat spikes are found ok.

New - 5" dia., Spruce double blazed & scribed "¼ S19 CS BT" bears N.28°W., 27.3 ft.

5" dia., D.Fir double blazed & scribed "¼ S30 CS BT" bears S.72°E., 20.0 ft.

Compass decl. 17½°E.