

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 16, 1866 (DCSO records Vol. 3 Page(s) 1155)

Set ¼ sec. post, from which
A crab Apple 5" dia., bears N.51°W., 122 lks. dist.
A Spruce 9" dia., bears S.35°W., 78 lks. dist.

Survey by Harry S. Hugill - For: Walter A Byritz - Jan. 15, 1949 - C.S. File 40/169

Set a 1¼" iron pipe from proportional measurement.
In open pasture, no reference points available.

Survey by Richard Hintz - For: International Paper Co. - Sept. 1976 - M 62-1

Found 1¼" Iron pipe.
New Bearing Object:
Utility pole, $\frac{10C}{22}$ bears N.2°W., 42.8 ft.

Fd. OK Nov. 16, 1978, K. Reed, DCSO - C.S. File 60/17-26

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 4/10/2002 - C.S. File 66/32-30

Found - 1¼" I.D. iron pipe in open field 2" below ground.
1949
Power pole 10C/22 bears N.2°W., 43.4 ft. to center at base (rec. N.2°W., 42.8 ft.) 1976
New - 25" dia., Spruce double blazed & scribed "¼ S18 CS BT" bears N.53½°W., 337.4 ft. (BT along S'ly R/W of Co. Rd.)
18" dia., Alder double blazed & scribed "¼ S18 CS BT" bears N.17°W., 249.0 ft. (BT along S'ly R/W of Co. Rd.)
Compass decl. 17½°E.

Fd. ok by C. Mulkins, 10/2004 - M145-74