

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 16, 1866 (DCSO records Vol. 3 Page(s) 1156)

-----

Set post for  $\frac{1}{4}$  sec. cor., from which  
A Fir 20" dia., bears N.67°W., 82 lks. dist.  
A Fir 15" dia., bears S.77°W., 81 lks. dist.

Survey by Robert B. Ward Jr. RLS #1091 - For: Champion International Corp. - Oct/Nov. 1984 - C.S. File 58/146-10 and M 97-79

-----

Found no trace of 1867 GLO corner or its accessories.  
At point of intersection measurement, SET a 2½" brass cap on a 2½" x 30" I.P. with the following accessories:  
12" Alder bears S.8°16'E., 38.1 ft. (1984 BT) bark scribed "¼ S18 BT"  
13" Alder bears N.57°19'W., 12.2 ft. (1984 BT) bark scribed "¼ S7 BT"