

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1251)

A Hemlock 15" dia., which I marked ¼ S on N. face, for ¼ sec. cor. from which

A Hemlock 9" dia., bears S.37°E., 9 lks. dist. mkd. ¼ S BT.

An Alder 15" dia., bears N.53½°W., 29 lks. dist. mkd. ¼ S BT.

Survey by Robert W. Ward, Jr. - For: Champion International Corp. - Aug. 1979 - M 78-76

Set 2½" brass cap attached to a 2½" galv. Iron pipe with flared bottom, from which

13" Alder bears S.30°59'E., 19.6 ft. bark scribed "N 1/4 S7 BT"

15" Fir bears N.62°55'W., 25.0 ft. scribed S1/4 S6 BT.

Troy Rambo - June 2001 - C.S. File 65/37-22A

Found - Brass cap set by R. Ward in 1979 from which:

An 18" DF with a healed face - bears N.62°55'W., 25.0 ft.

A 17" Alder with faint bark scribes - bears S.30°59'E., 19.6 ft.

Scribed- "¼ S7 BT" on a 12" Alder - bears S.28°W., 16.0 ft.

"¼ S7 BT" on a 14" Alder - bears S.62°E., 14.8 ft.

Jerry Estabrook - 9/26/2015 - C.S. File 65/89-58

Found - A 2½" brass cap on 2 1/2" iron pipe marked "T21S R11W S6 S7 1979 PLS1091" per M78-76.

A 20" fir stump with healed face and tag bears N.62°55'W., 25.0'.

A rotten alder blow down with no visible marks bears S.30°59'E., 19.6'.

New - An 8" fir face scribed "S¼ S6 BT" with X-chop and tag bears N.51°E., 11.40' to a spike at side center.

An 8" fir face scribed "S¼ S6 BT" with X-chop and tag bears N.59°W., 13.95' to a spike at side center.

Lat and Long per CARMEN ETREX hand held GPS

N 43°46'08.8" W 124°03'20.1"

Compass Declination 18° EAST

continued next page

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Stephen Stys - For: Rayonier - 10/2023 - M184-17 A&B

Found - A 2½" iron pipe w/2½" brass cap as set per M78- 76.
Set fiberglass rod alongside.

A 11" D.Fir, w/X-chop and tag bears N.51°E., 11.4'
(Per CS 65/89-58).

A 20"X6.5' tall D.Fir stump, w/healed face and tag
bears N.62°55'W., 25.0' (per M78-76).

A 10" D.Fir, w/X-chop and tag bears N.59°W., 13.95'
(Per CS 65/89-58).

LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS:

N:43°46'08.3" W:124°03'19.7".