

PRIMARY CORNER DESCRIPTION Center 1/4 Cor for Sec 6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Survey by Robert Ward Jr. - For: Champion International Corp.  
Aug. 1979 - M 78-76  
-----  
Set 2½" Brass cap attached to a 2½" x 30" galv. I.P. with flared bottom, from which  
    16" Fir bears N.31°00'W., 24.3 ft. scribed C ¼ S6 BT.  
    13" Fir bears N.38°00'E., 20.4 ft. scribed C ¼ S6 BT.

Tony Hostetter - For: Rome Creek Timber - Aug. 2019 - C.S. 65/103-12  
-----  
Found - 2½" iron pipe w/brass cap set by Ward in 1979 (M78-76) out of ground.  
Reset based on Wards distance from the E¼ corner and the BT N.36°E., from corner from which:  
    26" Fir stump, Ward BT, no marks, bears; N.35°E., [N38°E], 20.4 feet to center.  
    28" Fir stump, Ward BT, no marks, bears; N.29°W., 26.1 [N.31°W., 24.3'] feet to center  
New BTs- 12" Fir, marked "X", BT tag, bears; S.01°E., 19.8 feet to spike.  
          16" Fir, marked "X", BT tag, bears; S.51°W., 11.5 feet to spike.  
          16" Fir, marked "X", BT tag, bears; N.19°W., 2.5 feet to spike.

Stephen Stys - For: Rayonier - 10/2023 - M184-17 A&B  
-----  
Found - A 2½" iron pipe w/2½" brass cap as set per M78- 76. Set fiberglass rod alongside.  
          A 13" D.Fir, w/X-chop and tag bears S.1°E., 19.8' to spike (per CS/103-012).  
          A 17" D.Fir, w/X-chop and tag bears S.51°W., 11.5' to spike (per CS/103-012).  
          A 16" D.Fir, w/X-chop and tag bears N.19°E., 2.5' to spike (N.19°W., 2.5' per CS/103-012).  
New - A 19" D.Fir, faced & scribed "C ¼ S6 BT" with X-chop and tag bears S.86°E., 12.7' to a spike at side center.  
LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS:  
N:43°46'33.4" W:124°03'21.2".