

PRIMARY CORNER DESCRIPTION C C for Secs. 31 and 32 only (North)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1244)

I set a sandstone 30x18x10 ins., 23" in the ground, for closing cor. to secs. 31 and 32 marked C C with 1 notch on S. and 5 notches on E. edges, from which

A Maple 4" dia., bears N.71°E., 25 lks. dist. mkd. T21S R11W S31 and 32 CC BT.

A Maple 8" dia., bears S.68°W., 21 lks. dist. mkd. T21S R11W S31 BT.

And raised a mound of stone 1½ ft. high, 2 ft. base alongside.

Survey by Ronald Stuntzner - For: Moore Mill and Lumber Co. - June 20, 1979 - M 78-79

Set 5/8" Iron rod in mound of sandstone, from which

30" Maple bears S.3°E., 82.9 ft.

8" Alder bears S.39°E., 28.2 ft.

20" W.Fir bears N.32°30'W., 297.4 ft.

Survey by Ronald Stuntzner - For: Moore Mill & Lumber Co. - April 1984 - M 97-16

Set proportioned closing corner at point of true intersection with South bdy. of Sec. 30. No substantial evidence found of original C.C.

Set 5/8" x 30" Iron rod with plastic I.D cap mkd. "Stuntzner Engineering", from which

1979 BT, 20" W.Fir bears N.15°W., 203.0 ft., healed face.

New BT, 16" Alder bears S.49°E., 79.2 ft., barks scribed "T21S R11W S32 BT".

Note - This corner was not accepted by BLM in 1990 - 1995 resurvey, see information following.

BLM resurvey by Deborah M. Stephens and Harvey E. Wofford. Surveyed April 1990 thru April 1995 under group #1521. (DCSO records Vol. 51 Page(s) 19607-608)

Point for the closing cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

(Cont. Next Page)

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 158200

PRIMARY CORNER DESCRIPTION C C for Secs. 31 and 32 only (North)

Alias	Description

T21S R11W
S 30

S 31 S 32
C C
1991

from which

An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45° 00' E., 0.303 chs. dist., with brass cap mkd. T21S R11W S32 RM 20.0 FT 1991 and an arrow pointing to the true corner point.

Deposit a white "DEEP-1" magnetic marker at base of corner post.

From this point, a point established as the closing cor. of secs. 31 and 32 by Stuntzner in 1984, bears S. 43° 07' 30" W., 0.060 chs. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with plastic cap mkd. STUNTZNER ENGINEERING. This point is improperly positioned and not utilized in this survey, from which bearing trees mkd. by Stuntzner:

An alder, 18 ins. diam., bears S. 53½° E., 120 lks. dist., with scribe marks T21S R11W S32 BT visible in the bark.

A fir, 25 ins. diam., bears N. 14¼° W., 307½ lks. dist., with healed blaze.