

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1243)

Set a post, 4 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor. marked 1/4 S on W. face, from which
A Maple 30" dia., bears N.80°W., 35 lks. dist. mkd. 1/4 S BT
An Alder 15" dia., bears N.72 1/2°E., 44 lks. dist. mkd. 1/4 S BT.

Survey by Ronald Stuntzner - For: Moore Mill & Lumber Co. - June 20, 1979 - M 78-79

Set 5/8" Iron rod, from which
28" D.Fir bears S.82°W., 5.4 ft.
40" D.Fir bears S.61°E., 15.3 ft.

Survey by Ronald Stuntzner - For: Moore Mill & Lumber Co. - April 1984 - M 97-16

Set proportioned quarter corner, no evidence of original corner found and called gulch, course South did not fit field.
Set 5/8" x 30" Iron rod with plastic I.D. cap mkd. "Stuntzner Engineering", from which
40" D.Fir bears S.61°E., 59.3 ft. (1979 BT)
50" D.Fir bears S.38°E., 8.4 ft. scribed 1/4 S32 BT.

BLM resurvey by Deborah M. Stephens and Harvey E. Wofford. Surveyed April 1990 thru April 1995 under group #1521. (DCSO records Vol. 51 Page(s) 19610-11)

Found - iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with plastic cap mkd. STUNTZNER ENGINEERING, from which the remains of bearing trees mkd. by Stuntzner:

A fir stump, 42 ins. diam., bears S. 61° E., 90 lks. dist., with scribe marks 1/4 R11W visible in the bark.

A fir stump, 54 ins. diam., bears S. 38° E., 12 1/2 lks. dist., with scribe marks 1/4 BT visible in the bark.

At the corner point

(Cont. Next Page)

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T21S R11W
1/4
S 31 S 32
1991

No other suitable accessories available.

Deposit iron rod inside and white "DEEP-1" magnetic marker at base of stainless steel post.