

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29 & 30 only (South)

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1233)

Set a sandstone 12x8x8, 8" in the ground, for cor. to secs. 29 and 30, marked with 5 notches on N. and notch on E. edges, from which

A Maple 12" dia., bears N.13°E., 142 lks. dist. mkd. T21S R11W S30 BT.

and raised a mound of stone 1½ ft. high and 2 ft. base alongside; pits impracticable.

Survey by Richard J. Hintz - For: Champion International Corp. March 1978 - M 70-10

Set Iron pipe with brass cap, from which

20" Cedar bears S87°E., 106.8 ft., scribed.

28" Spruce bears S.52°E., 48.4 ft., scribed.

18" Maple bears N.66°30'W., 29.4 ft., scribed.

Survey by Donald L. Peel - For: Davidson Industries - March 30, 1982 - M 91-63

Set 1 5/8" x 36" I.P. with brass cap mkd. "PLS 752" as well as per the Manual.

New BT - 10" Maple bears N.41°E., 42.7 ft.

(3/4" Pipe of unknown origin bears S.51°48'39"W., 47.8 ft.)

Corner found and used in BLM resurvey by Deborah M. Stephens and Harvey E. Wofford. Surveyed April 1990 thru April 1995 under group #1521. (DCSO records Vol. 51 Page(s) 19606)