

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1232)

Set a post 3 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor. marked 1/4 S on W. face, from which

An Alder 24" dia., bears S.3°E., 45 lks. dist. mkd. 1/4 S BT
A Maple 24" dia., bears N.18 3/4°W., 204 lks. dist. mkd. 1/4 S BT.

Survey by Richard J. Hintz - For: Champion International Corp. - March 1978 - M 70-10

Set Iron pipe with brass cap, from which
36" W.Fir bears S.69°W., 40.4 ft., scribed.
60" Cedar bears S.31°30'E., 80.8 ft., scribed.

Survey by Richard J. Hintz - For: International Paper Co. - May 1982 - M 92-12 and M 92-11

Set 1 1/4" x 36" I.P. with brass cap stamped PLS 497. (Amended previous surveys), from which
62" Fir stump bears N.70°30'E., 34.0 ft., scribed.
24" Maple bears S.7°30'E., 68.1 ft., scribed.
The position of this corner changed.

Fd. OK, Nov. 1990 - M 111-9