

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1228)

Set a post 4 ft. long, 4" sq., 4" in the ground, for cor. to secs. 19, 20, 29 and 30, marked T21S S20 on NE.; R11W S29 on SE.; S30 on SW.; S19 on NW face, with 5 notches on E. and 2 notches on S. edges, from which

- A Fir 5" dia., bears N.21°E., 5 lks. dist. mkd. T21S R11W S20 BT.
- A Cedar 8" dia., bears S.32°E., 9 lks. dist. mkd. T21S R11W S29 BT.
- A Fir 4" dia., bears S.35°W., 5 lks. dist. mkd. T21S R11W S30 BT.
- An Alder 9" dia., bears N.89½°W., 4 lks. dist. mkd. T21S R11W S19 BT.

Survey by Harry S. Hugill - For: Walter A. Pyritz - Jan. 15, 1949 - C.S. File 40/169

Set from old BT.
Set 1¼" Iron pipe, from which
5" Fir bears N.21°E., 5 lks. dist. mkd. T21S R11W S20 BT.
(Now 7" in dia.)

Survey by Richard J. Hintz - For: Douglas County Land Dept. -April 15, 1975 - C.S. File 58/47

Found 1¼" iron pipe, from which
7" Fir bears N.21°E., 3.3 ft. Orig. BT.
14" Cedar bears N.1°E., 3.8 ft. to center, scribed S20 BT
18" Hemlock bears S.14½°W., 26.3 ft. to center, scribed S30 BT.
28" Hemlock bears S.81½°W., 30.3 ft. to center, scribed S30 BT.
40" Hemlock bears N.22¼°W., 31.8 ft. to face, scribed S19 BT.
Corner is approx. 420 ft. South of County Road #195 A.

Fd. OK, Nov. 1990 - M 111-9