

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated Dec 16, 1866 (DCSO rec. Vol. 3 Pg 1156)</p> <p>-----</p> <p>Set ¼ sec. post, from which</p> <ul style="list-style-type: none">A Bearberry 4" dia., bears N.78°W., 11 lks. dist.A Cedar 30" dia., bears S.65°E., 14 lks. dist.
<p>GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1227)</p> <p>-----</p> <p>The ¼ sec. cor. bet. secs. 19 and 20, being a post 4" sq., marked ¼ S on W. face, (evidently put up by the Co. Surveyor 2 years ago) and from which</p> <ul style="list-style-type: none">A Cedar 30" dia., bears S.65°E., 14 lks. dist. mkd. ¼ S BT <p>The other BT is gone.</p>
<p>Survey by Richard Hintz - For: Douglas County Land Dept. - April 15, 1975 - C.S. File 58/47</p> <p>-----</p> <p>Set Iron pipe with brass cap, from which:</p> <ul style="list-style-type: none">60" Fir bears N.65°W., 16.1 ft. to PK nail in face, scribed ¼ S19 BT.6" Fir bears N.42½°E., 14.6 ft. to center scribed ¼ S20 BT60" Fir stump bears N.16°E., 22.2 ft to center, not marked3' x 3' post bears S.49°W., 3.5 ft. <p>Corner is approx. 60 ft. West of County Road #195 A.</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 4/30/2002 - C.S. File 66/32-37</p> <p>-----</p> <p>Found - 2½" dia., unmarked brass cap on a 1½" O.D. iron pipe, protrudes 12" out of ground. 1975</p> <ul style="list-style-type: none">60" now 60" dia., dead D.Fir with a single unhealed blaze with visible scribing "¼S" and PK nail. PK nail bears N.65°W., 16.1 ft., root crown dist. 18.5 ft. 197560" dia., 3 ft. high unmarked D.Fir stump bears N.16°E., 22.2 ft. to center. 19756" now 12" dia., D.Fir with a fully healed single blaze bears N.42½°E., 14.6 ft. 1975 <p>New - 12" dia., Hemlock double blazed & scribed "¼ S20 CS BT" bears S.20°E., 11.5 ft.</p> <ul style="list-style-type: none">11" dia., Hemlock double blazed & scribed "¼ S19 CS BT" bears N.21°W., 6.0 ft. <p>Compass decl. 17½°E.</p>
<p>Fd. BC & BTs of rec. 4/2013 - by N. Hibbs, M165-17</p>