

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 & 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 16, 1866 (DCSO records Vol. 3 Page(s) 1155)

-----  
Set post for cor. to secs. 17, 18, 19 and 20, from which  
A Spruce 25" dia., bears N.42°W., 195 lks. dist.  
A Fir 4" dia., bears N.7°E., 95 lks. dist.  
A Spruce 27" dia., bears S.89°E., 652 lks. dist.  
A Spruce 7" dia., bears S.25°W., 243 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1246)

-----  
I return to the cor. of secs. 17, 18, 19 and 20, which I reestablish by setting a post, 4 ft. long, 4" sq., 24" in the ground, mkd. T21S S17 on NE.; R11W S20 on SE.; S19 on SW.; S18 on NW faces, with 3 notches on S. and 5 notches on W. edges, from which  
A Spruce 7" dia., bears S.25°W., 243 lks. dist. mkd. T21S R11W S19 BT.  
A stump of a Spruce bears N.42°W., 195 lks. dist., no marks visible.  
The other two bearing trees have been destroyed.

Survey by Harry S. Hugill - For: Walter A. Pyritz - Jan. 15, 1949 - C.S. File 40/169

-----  
Set 1½" Iron pipe from proportional measurements, from which  
42" Spruce on S. side of fence, bears N.27½°E., 72.3 ft.  
West corner gate post on E-W fence, bears N.52½°W., 139.7 ft.  
South edge of 2-story white house bears S.65°E.

Douglas County Surveyors Office - Gary L. Langlitz, P. Earle, crew - Nov. 7, 1974 - C.S. File 57/12-4

-----  
Found - 1½" I.P. buried approx. 5" in an open pasture.  
42" now 44" Spruce mkd. by Hugill in 1949, bears N.27½°E., 74.3 ft. (Rec. by Hugill is N.27½°E., 72.3 ft.) This tree has an unhealed blaze, we find no scribe marks. We rescribe to read "CSBT"  
A gate post in an E-W fence line noted by Hugill, bears N.52½°W., 139.7 ft.  
The white house used by Hugill for a bearing object is not visible.  
New BT - A 24" Spruce bears N.17°W., 94.6 ft. scribed "T21S R11W S18 CS BT"

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Fd. OK, Nov. 1982 by R. Geisler - M 93-34

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 4/17/2002 - C.S. File 66/32-31

-----  
Found - 1¼" iron pipe 5" below ground in pasture. 1949  
42" now 48" dia. down Spruce with an unhealed blaze,  
no scribing visible, root hole bears N.27½°E.,  
74.3 ft. 1949  
24" now 38" dia., Spruce with a fully healed double  
blaze bears N.17°W., 94.6 ft. 1974  
Gate post now gone.  
New - 13" dia., Alder double blazed & scribed "T21S R11W  
S20 CS BT" bears S.83°E., 352.6 ft.  
No other objects or trees within reasonable  
distance.  
Compass decl. 17½°E.