

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1252)

A Cedar 14" dia., which I marked $\frac{1}{4}$ S on E. face (W face not accessible on account of rock) for $\frac{1}{4}$ sec. cor., from which
A Fir 12" dia., bears N.55 $\frac{1}{2}$ °E., 12 lks. dist. mkd. $\frac{1}{4}$ S BT
A Cedar 16" dia., bears S.15 $\frac{1}{2}$ °W., 30 lks. dist. mkd. $\frac{1}{4}$ S BT.

Douglas County Surveyors Office - Gary L. Langlitz; Larry E. Monrean; P. Earle; S. Flause, crew - March 30, 1977 - C.S. File 59/32

1/4 Corner determined by DCSO survey (RM 3-13 & C.S. 60/12)
Set a 1" x 30" I.P. with brass cap attached 27" in the ground. Cap stamped Douglas County Surveyor
T 21 S R 11 W
1/4 S 6 S 5
1977

from which
A 11" Spruce bears N.88°E., 45.7 ft. Tree double blazed and scribed " $\frac{1}{4}$ S5 CS BT"
A Fir 16" bears N.27°W., 51.3 ft. Tree double blazed and scribed " $\frac{1}{4}$ S6 CS BT"

Tony Hostetter - For: Rome Creek Timber - Aug. 2019 - C.S. 65/103-12

(Condition report)
Found - 1977 DCSO brass cap (C.S. file 59/32). BTs are stumps no marks. From which:
8" Cascara, marked "X", BT tag, bears; N.0°26'E., 8.8 ft to spike.
10" Fir, marked "X", BT tag, bears; S.84°10'E., 7.1 feet to spike
10" Fir, marked "X", BT tag, bears; S.03°W., 7.0 feet to spike.
16" Fir, marked "X", BT tag, bears; N.66°W., 17.5 feet to spike.