

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 29 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1234)

-----  
Set a post 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on N. face, from which

A Fir 42" dia., bears S.14°E., 50 lks. dist. mkd. ¼ S BT

A White Fir 15' dia., bears N.40°W., 120 lks. dist. mkd. ¼ S BT.

Survey by Donald L. Peel, RLS #752 - Aug. 17, 1981 - C.S. File 58/229-13

-----  
Found - 63" Fir (orig. 42"), bark scribed, scribing visible, cruiser's mark on tree.  
24" rotted Fir stub, N.40°W., 79 ft. (slope dist., not horiz.) no marks visible, pretty well rotted away.

Set brass cap on 2½" Iron pipe mkd. "T21S R11W 1/4 S29 PLS 752 1981".

New BTs -29" Fir N.27°E., 32.2 ft.

63" Fir S.14°E., 33.0 ft., orig. BT.

Found and used in BLM resurvey by Deborah M. Stephens and Harvey E. Wofford, surveyed April 1990 thru April 1995 under group #1521. (DCSO records Vol. 51 Page(s) 19604-605)