

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 17

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 16, 1866 (DCSO records Vol. 3 Page(s) 1159)

Set ¼ sec. post, from which
A Fir 50" dia., bears S.75°E., 39 lks. dist.
A Hemlock 3" dia., bears N.32°E., 9 lks. dist.

Douglas County Surveyors Office - James W. Byron - M. Darby;
M. Stone; T. Connell - July 1965 - C.S. File 54/15

Set by proportionate measurement.
Set brass cap at cor. mkd: ¼ S 8 T21S R11W
17 County Surveyors Office
1965
New BTs -12" Hemlock bears N.35°E., 7.0 ft. mkd. ¼ S8 CS BT.
7" Hemlock S.6°W., 16.3 ft. mkd. ¼ S17 CS BT.
Corner falls 40 ft. North of top of slope of E-W ridge.

Fd. OK, July 1982 - M 93-10
Fd. OK, Oct. 1984 by R. Hintz - M 97-56

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 4/16/1998 - C.S. File 66/2-13

Found - 2½" dia., brass cap on a 1½" O.D. iron pipe, protrudes 3" above ground, properly marked. 1965
12" now 25" dia., Hemlock with a fully healed blaze bears N.35°E., 7.0' (Agrees w/rec.) 1965
7" now 19" dia., Hemlock with a fully healed blaze, bears S.6°W., 16.3' (Agrees w/rec.) 1965
New BTs- 16" dia., Hemlock, double blazed & scribed "¼ S8 CS BT" bears N.84°E., 5.2'.
7" dia., Hemlock, double blazed & scribed "¼ S17 CS BT" bears S.36°E., 11.8'.
Note - Corner lies 40' north of top of E-W ridge.