

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 262179

PRIMARY CORNER DESCRIPTION orig. CC for Secs. 32 & 33 only (north)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1242)

I set a post 4 ft. long, 4" sq., 24" in the ground, for closing cor. to secs. 32 and 33, marked CC T21S R11W on S.; S33 on E.; S32 on W. faces, with 1 notch on S. and 4 notches on E. faces, from which

A Vine Maple 4" dia., bears S.57°E., 25 lks. dist. mkd. T21S R11W S33 BT.

A Vine Maple 4" dia., bears S.66°W., 28 lks. dist. mkd. T2S R11W S32 BT.

A Spruce 42" dia., bears N.26°W., 27 lks. dist. mkd. T21S R11W CC S32 and 33 BT.

Survey by Warren D. Hootman #399 - For: Western Lane Logging Company - July 1, 1959 - C.S. File 51/30 and M 15-23

CC common to secs. 32 and 33 which is an angle iron set by Haines, from the original BTs.

Mark additional trees for this corner as follows:

Spruce 25" DBH, bears N.11°00'W., 34.2 ft.

Alder 35" DBH, bears S.24°30'W., 47.1 ft.

Survey by James W. Prochnau - For: U.S. Forest Service - Feb. 1984 - M 96-64 A&B and C.S. File 58/294

Note - Prochnau's survey sets a new closing corner which bears: N.2°40'43"W., 39.89 ft. dist. from original. See point identifier 262200 for additional information.

Found and used in BLM resurvey by Deborah M. Stephens and Harvey E. Wofford, surveyed April 1990 thru April 1995 under group #1521. (DCSO records Vol. 51 Page(s) 19602-603)