

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 300144

PRIMARY CORNER DESCRIPTION M.C on W. bdy. Sec. 33

Alias <u>891170</u>	Description <u>M.C. Right bank Umpqua River</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1874, - (DCSO records Vol. 3 Page(s) 1181)</p> <p>-----</p> <p>Marked a Fir 24" dia. on rocky bluff for meander post.</p>
<p>GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1241)</p> <p>-----</p> <p>Meander post on right bank of Umpqua River, to fractional secs. 32 and 33, which is a Fir 24" dia., mkd. MC on S. side, with T21S S33 on E.; R11W S32 on W. side.</p>
<p>Survey by Ronald Stutzner - For: Moore Mill and Lumber Co. - June 20, 1979 - M 78-79</p> <p>-----</p> <p>Set chipped "X" in rock face, from which 8" D.Fir bears N.44°E., 10.8 ft. 34" D.Fir bears East, 49.3 ft. Witness corner is a 5/8" Iron rod 11.05 ft. North of true corner.</p>
<p>Survey by James W. Prochnau, LS #1305 - For: U.S. Forest Service - Feb. 1984 - M 96-64 A & B and C.S. File 58/294</p> <p>-----</p> <p>Found - "X" chopped in rock face by Stuntzner, bears S.54°38'E., 0.38 ft. from true position. Stuntzner BT, 9" Fir bears N.44°E., 10.8 ft. healed face. Stuntzner BT, 34" Fir bears East, 49.3 ft., healed face. Stuntzner W.C., 5/8" Iron rod, 11.05 ft. North from "X". Iron rod is 0.80 ft. East of true line. Set Witness Corner, 3" alum. cap on 2½" x 30" alum. pipe, 11.27 ft. North on line from true position. Cap stamped per BLM manual and with PLS 1305. New BTs -10" Madrone bears N.73°W., 7.0 ft. scribed X BT. (scribed to W.C.) 8" D.Fir bears S.38°E., 11.1 ft. scribed X BT. (scribed to W.C.)</p>
<p>Found and used in BLM resurvey by Deborah M. Stephens and Harvey E. Wofford, surveyed April 1990 thru April 1995 under group #1521. (DCSO records Vol. 51 Page(s) 19600-601)</p>
<p>continued next page</p>

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 300144

PRIMARY CORNER DESCRIPTION M.C. on W. bdy. Sec. 33

Alias <u>891170</u>	Description <u>M.C. Right bank Umpqua River</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor,
& Richard Sanford, Surveying Technician, under Group #1644,
surveyed April 1992/May 1996. (DCSO records Vol. 53 Page(s)
20196)

The meander cor. of secs. 32 & 33 for the right bank of the
Umpqua River monumented with an X on a vertical rock bluff,
from which bearing trees mkd. by Stuntzner, reported by
Stephens and Wofford:

A fir, 12" diam., bears N.50°E., 16½ lks., with a healed
blaze.

A fir, 33" diam., bears N.88°E., 74½ lks., with a healed
blaze.