

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28 & 29 only (South)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1225)

Set a post 4 ft. long, 6" sq., 24" in the ground, for cor. to secs. 28 and 29 marked T21S on N. face; R11W S28 on E. face; S29 on W. face, with 4 notches on E. and 1 notch on S. edge, from which

- A Cedar 12" dia., bears N.10°E., 35 lks. dist. mkd. T21S R11W S28 BT.
- An Alder 12' dia., bears N.62°W., 27 lks. dist. mkd. T21S R11W S29 BT.

Survey by Ronald Stuntzner - For: Moore Mill & Lumber Co. - June 20, 1979 - M 78-79

Found - Orig. Red Cedar BT, now 34", bears N.10°E., 23.1 ft. Face open with brass washer "No. 238 Haines."
Set 5/8" Iron rod.
New BT - 44" Hemlock bears N.16°W., 55.2 ft.

Survey by James W. Prochnau, PLS #1305 - For: U.S. Forest Service - Feb. 1984 - M 96-63 A&B and C.S. File 58/294

Found - 5/8" iron rod set by Stuntzner.
Stuntzner BT, a 42" Hemlock bears N.14°W., 55.2 ft. (Rec. N.16°W.) visible scribing.
Orig. BT, a 36" Cedar bears N.10°E., 23.1 ft.
Set 3" alum. cap on 2½" x 30" alum. pipe. Cap stamped per BLM Manual and with "LS #1305". Rockmound. Buried iron rod.
New Accessories:
15" Hemlock bears N.70°W., 63.5 ft. scribed "T21S R11W S29 BT"
Reference monument, 2" alum. cap on 1/2" x 24" iron rod bears N.17°12'51"E., 50.17 ft. mkd. "RM SW S28 1984 PLS 1305 50.17" with arrow pointing to corner.

Corner found and used in BLM resurvey by Deborah M. Stephens and Harvey E. Wofford, surveyed April 1990 thru April 1995 under group # 1521. (DCSO records Vol. 51 Page(s) 19603)

Note - The corner is located in ravine, drains S.25°W.