

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1225)

A Fir 48" dia., which I marked ¼ S on E. side (a bluff prevents the W. side) for ¼ sec. cor. from which
A Fir 36" dia., bears S.3°E., 510 lks. dist. mkd. ¼ S BT
No tree within limits in sec. 29.

Wilford N. Haines - For: L & H Lumber Co. - 7/1967 (added 1/17/2024) - M34-30

Found snag of old corner tree.
¾" iron on East side. USFS had information that there was scribes on this snag.

Ernesto Alvarado, USFS, DCSO, Wit: Colin Long - Oct. 13, 1981 - C.S. File 61/29-9

CONDITION REPORT ONLY
Found - Orig. corner tree, 44" rotten D.Fir snag.
Brass cap on 1¼" I.P. set on map M 70-74, bears S.88°E., 4.0 ft. from tree, mkd. 1/4 S29 S28 1978.
3/4" I.P. set on map M 34-30, next to cap.
13" D.Fir bears N.48°E., 13.0 ft. scribing visible.
24" D.Fir bears S.9°W., 16.5 ft. scribing visible.
50" D.Fir stump bears S.3°E., 324.0 ft.
Location: Travel along Rd. #41, 1.1 miles past Otter Slough to location poster on Alder on West side of road; then go West 400 ft., then South 445 ft. to corner, which lies 30 ft. West of ridge top.

Survey by Richard J. Hintz - For: International Paper Co. - Dec. 1982 - M 93-47

Found - Orig. Fir corner tree, now a badly rotted 48" stub. Set 1¼" x 36" I.P. with brass cap stamped PLS 497, bears East 4.3 ft.,
New BTs -12" Fir bears N.52°E., 12.6 ft. to 50d nail in center.
18" Fir bears S.9°W., 16.6 ft. to 50d nail in center, scribed.
14" Fir bears S.25°E., 9.7 ft., overgrown blaze.
This map amends M 70-74.

(Cont. Next Page)

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 28 and 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by James W. Prochnau - For: U.S. Forest Service - Feb. 1984 - M 96-63 A&B and C.S. File 58/294

Found - Remains of orig. corner tree, a 44" rotten Fir snag.
2½" brass cap on 1¼" I.P. for W.C. set by Hintz, 4.3
ft. East of corner.
3/4" G.I.P. 0.3 ft West of cap set by Haines LS #239
on map M 34-30.
Hintz BT, 13" D.Fir bears N.48°E., 13.0 ft. (Rec.
N.52°E., 12.6 ft.) visible scribe.
Hintz BT, 24" D.Fir bears S.9°W., 16.5 ft. (Rec.
16.6 ft.) visible scribe.
Orig. BT, 50" D.Fir stump bears S.3°E., 324.0 ft.
(Rec. 510 lks.)
Set a reference monument, 3" alum. cap on 2½" x 30" alum.
pipe bears N.2°16'35"E., 58.72 ft. mkd. "RM WC ¼ S28 1984 PLS
1305 58.72" (with arrow point to corner)

Fd. as per record, T Hostetter, 12/2023 - M183-36