

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 16, 1866 (DCSO records Vol. 3 Page(s) 1157)

Set ¼ sec. post, from which
 A Vinemaple 4" dia., bears S.65°E., 4 lks. dist.
 A Fir 60" dia., bears N.85°W., 6 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1222)

The ¼ sec. cor. bet. secs. 20 and 21, which is a post, 4" sq., marked ¼ on W. face, from which
 A Fir 60" dia., bears N.85°W., 6 lks. dist. mkd. ¼ S BT.
 A Vinemaple 4" dia., bears S.65°E., 4 lks. dist.

Survey by Richard Hintz - For: International Paper Co. - Aug. 1977 - M 66-48

Found - Orig. 60" Fir, bears N.85°W., 4.0 ft., now rotted snag, 25 ft. high.
Set 5/8" Iron rod, from which
 36" Fir bears S.61°W., 36.2 ft., scribed.
 12' Hemlock bears S.7°30'W., 51.0 ft., scribed.

Fd. ok by T. Rambo, 3/2004 & 11/2008 - M158-19