

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 16, 1866 (DCSO records Vol. 3 Page(s) 1159)

Set post for cor. to secs. 8, 9, 16 and 17, from which
A Fir 30" dia., bears N.75°W., 35 lks. dist.
A Fir 24" dia., bears N.30°E., 14 lks. dist.
A Fir 18" dia., bears S.65°E., 37 lks. dist.
A Fir 30" dia., bears S.55°W., 24 lks. dist.

F.C. Frear, Deputy Co. Surveyor - Wit: W.F. Peck and Cowan - May 17, 1918 - Vol 3 Pg 28; F.B. 45 Pgs. 6-9 and ("old" corner book, Pg. 16)

Renew cor. from four Fir stumps of old BTs.
Set in 6" x 48" Chittem stake, from which
A 10" Chittem bears S.14°E., 0.435 chs.
A 10" Fir bears S.41°W., 0.25 chs.

Douglas Co. Surveyors Office - James W. Byron Deputy - For: Oregon State Game Dept. - Sept. 1959 - C.S. File 49/186 and M 15-63

Found - 1½" Iron pipe with plug mkd: $\frac{S\ 8}{S17} | \frac{S\ 9}{S16}$
Found stump of 3 original BTs and Frear's SW BT.'
New BTs - 36" R.Fir S.11°30'W., 79.6 ft. scribed S17 T21S R11W CS BT.
(?) R.Fir bears S.26°E., 107.4 ft. scribed S16 T21S R11W CS BT.

Douglas Co. Surveyors Office - James Byron, Co. Surveyor - M. Darby; M. Stone; T. Connell, crew - July 1965 - C.S. File 54/15

Found - 1½" I.Pipe with cap 4 ft. above ground.
36" Fir S.11½°W., 79.6 ft.
Other BTs gone.
New BT - 10" Alder, forked, bears N.70°W., 5.5 ft. scribed S8 CS BT.

Douglas Co. Surveyors Office - R.B. Kimberling; F.C. Silagy, crew - March 22, 1978 - C.S. File 59/46-29

Found - 1½" I.P. with a steel plug set 4 ft. above ground marked 8, 9, 17, 16 in a 24" dia. mound of stone.
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Orig. 30" now 27" rotted Fir stump bears N.74°W., 23.9 ft. @+33°=20 ft. (Rec. N.75°W., 23.1 ft.) with scribing "BT"

A 24" Fir stump bears N.23°E., 10.1 ft. (Rec. N.30°E., 9.2 ft.)

A 30" now 37" Fir stump bears S.55°W., 16.5 ft. (Rec. 15.8 ft.) with visible scribing "S17 BT"

A 10" now 17" Fir snag, 12 ft. tall, bears S.41°W., 16.5 ft. with chopped open, rotted blaze.

A 36" now 39" D.Fir bears S.15°W., 80.9 ft. (Rec. S.11°30'W., 79.6 ft.) with a well healed single blaze.

A 24" Fir snag, 18 ft. high, bears S.22°E., (Rec. S.26°E.) 107.4 ft. with scribing "11 S16 CS BT" in a partly healed double blaze.

A 10" now 11" Alder is down and has a rooted face, orig. position bears approx. N.70°W., 5.5 ft.

Reset 1½" I.P. on West edge of brass cap with plug 3 ft. above ground. At corner point I SET a 1" x 36" I.P. with brass cap set at ground level mkd: Douglas County Surveyor

T 21 S R 11 W	
S 8	S 8
S 17	S 16
1978	

New BTs -18" Maple bears S.68½°E., 36.5 ft. @-34°=30.3 ft. I double blaze and scribe T21S R11W S16 CS BT.

20" Alder bears N.13°W., 52.7 ft. I bark scribe T21S R11W S8 CS BT.

Survey by Ronald G. Geisler - For: Champion International Corp. - Nov. 1982 - C.S. File 58/278

Found - 1978 DCSO brass cap and a plugged 1½" I.P. extending 2.8 ft. above ground, on the West edge of the brass cap.

28" rotten Fir stump bears N.74°W., 19.3 ft. (orig. rec. N.75°W., 23.1 ft.) scribed BT.

24" rotted Fir stump bears N.23°E., 10.1 ft. (orig.) (Rec. N.30°E., 9.2 ft.) No scribing visible.

36" Fir stump bears S.58°W., 16.3 ft. (orig.) (Rec. S.55°W., 15.8 ft.) Scribed S17 BT.

14" rotten Fir stump bears S.69°E., 23.6 ft. (orig.) (Rec. S.65°E., 24.4 ft.) No scribing visible.

17" Fir snag 15 ft. tall, bears S.41°W., 16.5 ft. (1918) Chopped open, rotted blaze.

48" Fir bears S.15°W., 81.7 ft. (Rec. S.11½°W., 79.6 ft.) X bark scribed alongside healed blaze. (1959). (Cont. Next Page)

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

24" Fir snag, 18 ft. tall, bears S.22°E., 107.4 ft.
(1959) (Rec. S.26°E.) Scribe marks visible.
18" Maple bears S.68½°E., 32.7 ft. (Rec. 30.3 ft.)
Scribed T21S R11W S16 CS BT. (1959)
21" Alder bears N.13°W., 52.0 ft. (Rec. 52.7 ft.)
Bark scribed T21S R11W S8 CS BT.
New BT - 12" forked Alder bears N.54°E., 50.6 ft. Bark
scribed T21S R11W S9 BT.

Fd. OK - Jerry Lee Estabrook - June 1996 - M125-23