

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 16, 1866 (DCSO records Vol. 3 Page(s) 1160)

Set ¼ sec. post, from which
A Fir 28" dia., bears N.55°E., 28 lks. dist.
A Hemlock 9" dia., bears N.35°W., 34 lks. dist.

Douglas County Surveyors Office - James W. Byron, V. Tracy and crew - June 1967 - C.S. File 54/47 and M 33-18

(From Hub #52-A, we go N.41°42'50"W., 56.0 ft. to proportional point for ¼ corner. Sketch in C.S. File)
Set brass cap at corner mkd: County Surveyors Office
T 21 S R 11 W
1/4 S8|S9
1967

From our corner:
A 40" Fir stump, N.28°E., 9.0 ft., no scribe found. This is remains of tree called for in Forest Appraisal notes, 1954, by E.D. Stroup.
No trace of NW. original BT.
New BTs:
5" hemlock N.8°W., 103.3 ft. mkd. ¼ S8 CS BT.
4" Alder N.25°E., 42.2 ft. mkd. ¼ S9 CS BT.
This corner lies on top of spur ridge, course West.

Douglas County Surveyors Office - Karen Reed; John Powell, R. Smith, crew - Feb. 22, 1982 - C.S. File 61/30-14

Found - 1967 DCSO brass cap properly marked, being 1 ft. above ground.
A 4" Alder now 9", bears N.25°E., 42.2 ft. with visible scribe "BT" in a double blaze.
A 5" Hemlock now a 14" Hemlock in a group of four from an old stump bears N.8°W., 103.3 ft. with well healed double blaze.
The remains of an old Fir stump bears N.28°E., 9.0 ft. This stump called in 1967 Byron visit.
No original BTs found.
Left brass cap in place.
New BTs -A 7" D.Fir bears S.6°E., 13.4 ft. scribed "¼ S9 CS BT" in a double blaze.
An 8" D.Fir bears N.87°W., 20.4 ft. scribed "¼ S8 CS BT" in a double blaze.
Corner located on top of spur ridge course West. Flagged and tagged all BTs.

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs., 8 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 4/14/1998 - C.S. File 66/2-12

Found - 2½" dia., brass cap on a 1½" O.D. iron pipe, protrudes 13" above ground, properly marked. 1967
4" now 10" dia., dead Alder with a partially healed double blaze, illegible scribing vis., bears N.25°E, 42.2' (agrees w/rec.) 1967
5" now 23" dia., Hemlock with a fully healed double blaze, bears N.8°W., 103.3', (Agrees w/rec.) 1967
Remains of old Fir stump, bears N.28°E., 9.0' (Agrees w/rec.) ?
7" now 11" dia., D.Fir with a fully healed double blaze bears S.6°E., 13.4' (Agrees w/rec.) 1982
8" now 12" dia., D.Fir with a fully healed double blaze bears N.87°W., 20.4' (Agrees w/rec.) 1982
New BT - 16" dia., Hemlock, double blazed and scribed "¼ S9 CS BT" bears N.10°E., 11.9'.
Note - Corner lies on a flat portion of an East-West ridge, approx. 30' North of South edge.