

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 16, 1866 (DCSO records Vol. 3 Page(s) 1160)

- 
- Set post for cor. to secs. 4, 5, 8 and 9, from which
- A Fir 20" dia., bears N.29°W., 14 lks. dist.
  - A Fir 36" dia., bears N.56°E., 13 lks. dist.
  - A Fir 36" dia., bears S.50°E., 23 lks. dist.
  - A Fir 18" dia., bears S.70°W., 20 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1244-45)

- 
- Cor. to secs. 4, 5, 8 and 9, which is a post, decayed, 4" sq., mkd. T21S S4 on NE.; R11W S9 on SE.; S8 on SW.; S5 on NW. faces, with 5 notches on S. and 4 notches on E. edges; from which
- A Fir 36" dia., bears N.56°E., 13 lks. dist. mkd. T21S R11W S4 BT.
  - A Fir 36" dia., bears S.50°E., 23 lks. dist. mkd. T21S R11W S9 BT.
  - A Fir 18" dia., bears S.70°W., 20 lks. dist. mkd. T21S R11W S8 BT.
  - A Fir 20" dia., bears N.29°W., 14 lks. dist. mkd. T21S R11W S5 BT.

Douglas Co. Surveyors Office - James Byron - V. Tracy; J. Heritage; E. West - June 1967 - C.S. File 54/47 and M 33-18

-----

Found Orig. BTs as follows, with ring count indicating they were mkd. about time Thiel was here in 1891. Scribe appears same as found in other parts of county by Thiel:

- 12" Spruce stump S.67°E., 8.6 ft. unrecorded "9BT" and fragmentary scribe.
- 22" Fir stump S.87°W., 3.0 ft. unrecorded "S8" scribe on log that was cut from stump.
- 46" Fir stump N.37°W., 35.3 ft. unrecorded "T21S R11W S5 BT" scribe.
- 40" Fir stump N.33°E., 42.2 ft. unrecorded "T21S R11W S4 BT" scribe.
- 50" Fir stump S.70°W., 13.2 ft. no scribe, possible original BT by Meldrum.

Possible stump holes for SE and NW original BT locations. Call on creek to West and ridge top to North fit very well.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Set Brass cap at cor. mkd: County Surveyors Office  
T 21 S R 11 W  
S 5 S 4  
S 8 S 9  
1967

New BTs:  
9" D.Fir S.17°E., 16.4 ft. mkd. T21S R11W S9 CS BT.  
18" D.Fir S.41°W., 11.6 ft. mkd. T21S R11W S8 CS BT.  
15" D.Fir N.87°W., 25.5 ft. mkd. T21S R11W S5 CS BT.  
14" D.Fir N.52½°E., 37.7 ft. mkd. T21S R11W S4 CS BT.  
This corner lies on moderate S. slope 224 ft. E. of creek, 2 ft. wide, course South.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 4/6/1998 - C.S. File 66/2-10

-----  
Found - 2½" dia., brass cap on a 1½" O.D. iron pipe, protrudes 11" above ground, properly mkd. 1967  
9" now 10" dia., 12 ft. high, D.Fir snag with a fully healed double blaze bears S.17°E., 16.4 ft. (Agrees with rec.) 1967  
18" now 24" dia., down D.Fir with a fully healed double blaze, rot hole near rec. "S.41°W., 11.6 ft. 1967  
15" now 20" dia., down D.Fir with a fully healed double blaze, roothole near rec. "N.87°W., 25.5 ft."  
14" now 18" dia., down D.Fir with a fully healed double blaze, roothole near rec. "N.52½°E., 37.7 ft."  
16" dia., 2 ft. high decayed D.Fir, no blazes or scribing visible, bears S.87°W., 3.0 ft. (Agrees with 1967 rec).  
Unrecorded SE BT noted in 1967, now gone.  
33" dia., 6 ft. high D.Fir stump with visible scribing "T21S R11W S5 BT" bears N.37°W., 35.3 ft. (Agrees with 1967 rec.)  
36" dia., 4 ft. high D.Fir stump with visible scribing "T21S R11W S4 BT" bears N.33°E., 42.2 ft. (Agrees with 1967 Rec.)  
Rotted D.Fir remains near rec. "S.70°W., 13.2 ft."  
New BTs- 17" dia., D.Fir, double blazed and scribed "T21S R11W S4 CS BT" bears N.50°E., 59.1 ft.  
18" dia., D.Fir, double blazed and scribed "T21S R11W S9 CS BT" bears S.79°E., 27.5 ft.  
24" dia., D.Fir, double blazed and scribed "T21S R11W S8 CS BT" bears S.73½°W., 24.6 ft.

(Cont. next page)

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

12" dia., D.Fir, double blazed and scribed "T21S  
R11W S5 CS BT" bears N.68½°W., 44.4 ft.  
Corner lies on a gradual south slope in high dense  
undergrowth within an area of multiple wind fallen firs.