

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 28 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1227)

Set a sandstone 11x11x5 ins., 8" in ground, for ¼ sec. cor. marked ¼ S on N. face, and raised a mound of stone, 1½ ft. high and 2 ft. base alongside; pits impracticable.

Survey by James W. Prochnau, LS #1305 - For: U.S. Forest Service - Feb. 1984 - M 96-63 A&B and C.S. File 58/294

Set 3" alum. cap on 2½" x 30" alum. pipe with cap stamped per BLM Manual and with PLS 1305. Rock mound.
New BTs -34" D.Fir bears N.2°W., 12.1 ft. scribed ¼ S28 BT.
21" D.Fir bears N.60°E., 18.6 ft. scribed ¼ S28 BT.

Fd. & used on Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, & Richard Sanford, Surveying Technician, under Group #1644, surveyed April 1992/May 1996. (DCSO records Vol. 53 Page(s) 20199)