

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 21

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 16, 1866 (DCSO records Vol. 3 Page(s) 1158)

Set ¼ sec. post, from which
A Maple 15" dia., bears S.86°W., 106 lks. dist.
An Alder 18" dia., bears N.10°E., 11 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page 1216 and Page 1217)

(Page 1216)
I cannot find the bearing trees or ¼ sec. cor. post.
Page 1217)
Set a post 4 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S. on N. face, from which
A Cedar 24" dia., bears N.65½°W., 112 lks. dist. mkd. ¼ S BT.
A Maple 24" dia., bears S.86½°W., 110 lks. dist. mkd. ¼ S BT.
Close by this latter is a stump of a decayed maple of the dia., which was probably the former bearing tree.

Survey by Richard Hintz - For: International Paper Co. - Aug. 1977 - M 66-48

Set 5/8" Iron rod, from which
28" Cedar stump bears N.77°19'E., 57.87 ft. scribed.
(Dist. and bearing to 60 penny nail in face.)
6" Alder bears S.2°E., 7.9 ft. scribed.
Corner is 3 ft. East of a creek, course N.20°E.

Survey by Richard J. Hintz - For: International Paper Co. - May 1982 - M 92-12

Found 5/8" Iron rod, from which
28" Cedar stump bears N.77°19'E., 57.87 ft. to face.
6" Alder bears S.2°E., 7.9 ft., uproot.
New BT:
22" Hemlock bears N.46°W., 66.0 ft., to face, scribed.