

PRIMARY CORNER DESCRIPTION C C for Secs. 33 & 34 only (North)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1241)

-----  
Set a sandstone 14x11x4 ins., 10" in the ground, for closing cor. to secs. 33 and 34, marked C C with 1 notch on S. and 3 notches on E. edges, and raised a mound of stone, 1½ ft. high and 2 ft. base alongside; pits impracticable.

Survey by Warren D. Hootman #399 - For: Western Lane Logging Company - July 1, 1959 - C.S. File 51/30 and M 15-23

-----  
I set this cornr 2,676.3 ft. South of the ¼ cor. for secs. 27 and 28 and 4,026.0 ft. East of South corner of secs. 28 and 29, T21S R11W.

Drove a 1" Iron rod and marked BTs as follows:

D.Fir 32" DBH, bears S.39°30'E., 58 ft.

D.Fir 23" DBH, bears S.65°30'W., 25.7ft.

D.Fir 12" DBH, bears N.19°30'E., 40.7 ft.

Survey by James W. Prochnau - For: U.S. Forest Service - Feb. 1984 - M 96-63 A&B and C.S. File 58/294

-----  
Found - 1" Iron pipe set by Hootman, bears S.3°05'28"E., 18.82 ft. from true position.

Hootman BT, a 36" D.Fir snag bears S.39°E., 58.0 ft. Healed face.

Hootman BT, a 24" D.Fir bears S.65°W., 26.0 ft. healed face.

Hootman BT, a 12" D.Fir bears N.19°E., 41 ft.

Set at true position, 3" alum. cap on 2½" x 30" alum. pipe with cap stamped per BLM Manual and with PLS 1305. Rock mound.

New BTs -24" D.Fir bears S.38°W., 37.5 ft. scribed T21S R11W CC S33 BT.

34" D.Fir bears S.58°E., 65.0 ft. scribed T21S R11W CC S34 BT.

Hootman BTs bear from pipe.

Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, & Richard Sanford, Surveying Technician, under Group #1644, April 1992/May 1996. (DCSO records Vol. 53 Page(s) 20192-3)

-----  
The closing cor. of secs. 33 & 34, reestablished using proportionate measurement by Prochnau, in 1984. There is no remaining evidence of the original corner, therefore this position is accepted as the corner; monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with aluminum cap mkd. continued next page

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 362200

PRIMARY CORNER DESCRIPTION C C for Secs. 33 & 34 only (North)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

T21S R11W  
S 28  
S 33 S 34  
C C  
1984  
PLS 1305

from which bearing trees mkd. by Prochnau  
A fir, 27" diam., bears S.38°W., 57 lks., with healed blaze.  
A fir, 39" diam., bears S.59½°E., 98 lks., with healed blaze.

From this point, a point established as the closing cor. of secs. 33 & 34 by Hootman, in 1959, bears S.4°32'30"E., 0.277 chs. This point was established using erroneous control and is not utilized in this survey; monumented with an iron pipe, 1" diam., loosely set, lying on its side, from which bearing trees mkd. by Hootman:

A fir, 12" diam., bears N.16°E., 62 lks., with healed blaze.  
A fir, 36" diam., bears S.40°E., 86 lks., with healed blaze.  
A fir, 27" diam., bears S.64°W., 40 lks., with healed blaze.