

PRIMARY CORNER DESCRIPTION Wit. Cor. for the ¼ cor. Secs. 27 & 28

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1221)

Set Witness Corner 321 lks. West of true ¼ sec.cor., set a sandstone 10x8x7 ins., 7" in the ground, marked ¼ W C on W. face, from which

A Fir 52" dia., bears East, 2 lks. dist., mkd. ¼ S WC BT

A Fir 30" dia., bears West 12 lks. dist., mkd. ¼ S WC BT

The place of true corner is bedrock.

Survey by H.T. Lewis - April 18, 1939 - C.S. File 16/55 and ("old" corner Vol. 1 Pg. 15)

I found the witness corner to the ¼ cor. bet. 27 and 28. I could not find the stone as described in the govt. field notes, but found two dead witness trees in place, I therefore set Cedar post 4 ft. long, 4" dia., 18" in ground mkd. ¼ S W.C., from which

A Fir 16" dia., bears S.79°E., 23 ft. mkd. ¼ S W.C. BT 722.

A Fir 12" dia., bears S.9°W., 5 ft. mkd. ¼ S W.C. BT 722

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #430, Surveyed June/Aug 1960 (DCSO records Vol. 31 Page(s) 12897-98)

The record witness cor. for the ¼ sec. cor. determined at record bearing from the remains of the original bearing trees:

A Fir snag 72" dia., bears N.58½°E., 7 lks. dist. with scribe mark 4 visible on bark blaze. (Rec. dist. 2 lks.)

A Fir snag 35" dia., bears S.82½°W., 15 lks. dist. with no marks remaining on bark blaze. (Rec. dist. 12 lks.)

and two bearing trees of which I have no record:

A Fir 25" dia., bears S.44¼°E., 5 lks. dist. with healed double blaze. I open and uncover scribe mark S.

A Fir 18" dia., bears S.18°W., 36 lks. dist. with healed double blaze.

At the corner point, which is on top of spur, slopes N. Set an iron pipe 16" long, 1" dia., 14" in the ground to perpetuate the witness corner point.

(Cont. Next Page)

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 379240

PRIMARY CORNER DESCRIPTION Wit. Cor. for ¼ cor. secs. 27 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by James W. Prochnau, LS #1305 - For: U.S. Forest Service - Feb. 1984 - M 96-61 A&B and C.S. File 58/294

Found - 3/4" galv. I.P. set by BLM.
Orig. BT, 69" burned Fir snag bears N.58½°E., 5.4 ft. (Rec. East, 2 lks.)
24" Fir snag bears S.82°W., 9.5 ft. (Rec. West, 12 lks.) Orig. BT.
Unrecorded 18" D.Fir bears S.18°W., 24.6 ft., healed face.
Unrecorded 33" D.Fir bears S.30°E., 1.9 ft. healed face.
Replaced pipe with 2" alum. cap on 1/4" x 18" rod in root structure of BT. Cap stamped per BLM Manual and with "PLS 1305".

Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, & Richard Sanford, Surveying Technician, under Group #1644, surveyed April 1992/May 1996. (DCSO records Vol. 53 Page(s) 20194-5)

The original witness corner to the 1/4 sec. cor. of secs. 27 & 28, remonumented by Prochnau, in 1984; monumented with a 1½ aluminum post, firmly set flush with the ground, with aluminum cap mkd.

T21S R11W
WC
¼
S 28 | S 27
1984
PLS 1305

from which the remains of the original bearing trees
A fir snag, 72" diam., bears N.58½°E., 7 lks., with healed blaze.
A fir snag, size indeterminate, bears S.82½°W., 15 lks., no visible marks.
and BT mkd. by person(s) unknown, reported by Brooks
A fir, 35" diam., bears S.44½°E., 3 lks., with healed blaze. (Record, 5 lks.)
A fir, 19" diam., bears S.18°W., 36 lks., with healed blaze.