

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27 and 28 only (South)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1221)

-----  
Set a sandstone 12x10x5 ins., 8" in the ground, for cor. to secs. 27 and 28, marked with 1 notch on S. and 3 notches on E. edges and raised a mound of stone 1½ ft. high and 2 ft. base alongside; pits impracticable.

Survey by Warren D. Hootman #399 - For: Western Lane Logging Co. - July 1, 1959 - M 15-23 and C.S. File 51/30

-----  
Drove a pipe and marked the following bearing trees:  
Cedar 14" DBH, bears S.6°00'E., 16.3 ft.  
D.Fir 19" DBH, bears N.86°00'W., 15.0 ft.  
D.Fir 24" DBH, bears N.50°30'E., 7.2 ft.

Survey by James W. Prochnau - For: U.S. Forest Service - Feb. 1984 - M 96-61 A&B and CS File 58/294

-----  
Set 2" alum. cap on 2½" x 30" alum. pipe. Cap stamped per BLM Manual and with "PLS 1305". Rock mound.  
New BTs -7" D.Fir bears N.67°W., 6.9 ft. scribed T21S R11W S28 BT.  
7" D.Fir bears N.21°E., 26.9 ft. scribed T21S R11W S27 BT.

Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, & Richard Sanford, Surveying Technician, under Group #1644, surveyed April 1992/May 1996. (DCSO records Vol. 53 Page(s) 20193-4)

-----  
From the cor. of secs. 27 & 28 only, reestablished using two point control by Prochnau, in 1984. There is no remaining evidence of the original corner, therefore this position is accepted as the corner; monumented with an aluminum post, 2½" diam., firmly set, projecting 4" above ground, with aluminum cap mkd.

T 29 S R 10 W  
S 28 S 27  
1984  
PLS 1305

from which bearing trees mkd. by Prochnau  
A fir, 14" diam., bears N.19°E., 40½ lks., with a healed blaze.  
A fir, 14" diam., bears N.67°W., 12 lks., with a healed blaze.

continued next page

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27 and 28 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From this point, a point established as the cor. of secs. 27 and 28 only by Hootman, in 1959, bears S.14°24'00"W., 0.523 chs. This point was established using improper control and is not utilized in this survey; determined from the remains of bearing trees mkd. by Hootman:

A cedar snag, 15" diam., bears S.6°E., 25 lks., with scribe marks BT 33 T29 visible on partially open blaze.

A fir stump, 14" diam., bears N.86°W., 23 lks., no marks visible on open decayed blaze.