TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1221)

The place of true corner is bedrock.
Set Witness Corner 321 lks. West of true ¼ sec. cor. (See Cor. description #397240)

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #430, Surveyed June/Aug 1960 (DCSO records Vol. 31 Page(s) 12897)

At point for the ¼ sec. cor. of secs. 27 and 28, established at record bearing and distance from the record witness corner for the ¼ sec. cor.
Set an iron post 28" long, 2½" dia., 22" in the ground, with brass cap mkd:

¼
S 28 S 27
T 21 S R 11 W
1960

from which
A Cedar 38" dia., bears N.37½°E., 172 lks. dist. mkd. ¼ S27 BT.
A Cedar 12" dia., bears N.44°W., 66 lks. dist. mkd. ¼ S28 BT.
Corner is 30 lks. West of ravine, course N.10°E.

Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, & Richard Sanford, Surveying Technician, under Group #1644, surveyed April 1992/May 1996. (DCSO records Vol. 53 Page(s) 20194)

The ¼ sec. cor. of secs. 27 & 28, monumented with an iron post, 2½" diam., firmly set, projecting 8" above ground, with brass cap mkd.

1/4
S28 S27
T21S R11W
1960

from which bearing trees mkd. by Brooks
A cedar, 54" diam., bears N.39½°E., 155 lks., with healed blaze. (Record, N.37½°E., 172 lks.)
A cedar, 27" diam., bears N.44° 63½ lks., with healed blaze. (Record, 66 lks.)