

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1219)

-----  
Set a post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 21, 22, 27 and 28, marked T21S S22 on NE.; R11W S27 on SE.; S28 on SW.; S21 on NW. faces, with 3 notches on E. and 2 notches on S. edges, from which

A Fir 36" dia., bears S.5°W., 276 lks. dist. mkd. T21S R11W S28 BT.

A Maple 8" dia., bears N.53°W., 14 lks. dist. mkd. T21S R11W S21 BT.

No other trees within limits and I raised a mound of stone, 1½ ft. high and 2 ft. base alongside; pits impracticable.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #430, Surveyed June/Aug 1960 (DCSO records Vol. 31 Page(s) 12898)

-----  
Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 20" long, 1" dia., 8" in the ground and 3" in drill hole in solid rock, with brass cap mkd:

T 21 S R 11 W  
S 21 S 22  
S 28 S 27  
1960

from which

A Fir 10" dia., bears N.37½°E., 27 lks. dist. mkd. T21S R11W S22 BT.

A Maple 12" dia., bears S.79 3/4°E., 62 lks. dist. mkd. T21S R11W S27 BT.

A Cedar 8" dia., bears S.30°W., 66 lks. dist. mkd. T21S R11W S28 BT.

A Fir 11" dia., bears N.59°W., 61 lks. dist. mkd. T21S R11W S21 BT.

Fd. OK, Feb. 1984 by J. Prochnau - M 96-61 A&B