

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1218)

Set a post 3 ft. long, 4" sq., 18" in the ground for ¼ sec. cor. marked ¼ S on W. face, from which

An Alder 6" dia., bears N.78°W., 14 lks. dist. mkd. ¼ S BT.

A Cherry 8" dia., bears S.84½°E., 18 lks. dist. mkd. ¼ S BT.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #430, Surveyed June/Aug 1960 (DCSO records Vol. 31 Page(s) 12901)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼
S 21 S 22
T 21 S R 11 W
1960

from which

A Cedar 5" dia., bears S.67°E., 8 lks. dist. mkd. ¼ S22 BT

A Fir 48" dia., bears S.67°W., 51 lks. dist. mkd. ¼ S21 BT