

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1214-15)

-----  
Set a post 4½ ft. long, 5" sq., 24" in the ground for cor. to secs. 15, 16, 2 and 22, marked T21S S15 on NE.; R11W S22 on SE.; S21 on SW.; S16 on NW. faces, with 3 notches on E. and S. edges, from which  
A Cedar 36" dia., bears N.52°E., 20 lks. dist. mkd. T21S R11W S15 BT.  
An Alder 15" dia., bears S.42°E., 31 lks. dist. mkd. T21S R11W S22 BT.  
A Hemlock 6" dia., bears S.10°W., 15 lks. dist. mkd. T21S R11W S21 BT.  
A Hemlock 16" dia., bears N.56°W., 37 lks. dist. mkd. T21S R11W S16 BT.

BLM resurvey by Thomas A. Tillman, Civil Engineer (Cadastral), under Group #373, under Special Instructions dated Aug. 6, 1957 - (DCSO records Vol. 29 Page(s) 12335)

-----  
The sec. cor., remonumented with an iron pipe, 2 ft. long, 1¼" dia., driven 18" in the ground, from which the original bearing trees:  
A Cedar 66" dia., bears N.54°E., 20 lks. dist., plainly blazed and healed. (Rec. brg. N.52°E.)  
An Alder 20" dia., bears S.42°E., 24 lks. dist., plainly blazed and healed. (Rec. dist. 31 lks.)  
A Hemlock snag 16" dia., bears S.6½°W., 15 lks. dist. with scribe marks "BT" visible on opened blaze. (Rec. brg. S.10°W.)  
A Hemlock snag 36" dia., bears N.56°W., 35 lks. dist. with scribe marks "R11W" and "BT" visible on opened blaze. (Rec. dist. 37 lks.)

At the corner point  
Set an iron post, 30" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:  
T21S R11W  
S 16 S 15  
S 21 S 22  
1957

from which new bearing trees  
A Hemlock 9" dia., bears S.12°E., 35 lks. dist. mkd. T21S R11W S22 BT.  
A Hemlock 16" dia., bears S.27¼°W., 133 lks. dist. mkd. T21S R11W S21 BT.  
A crooked Cedar 17" dia., bears N.33 3/4°W., 181 lks. dist. mkd. T21S R11W S16 BT.  
Reset the iron pipe alongside the iron post.

PRIMARY CORNER DESCRIPTION Sec. cor. for 15, 16, 21 and 22

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Fd. and used in BLM resurvey by Floyd Brooks, under Group #430. Surveyed 1960 (DCSO records, Vol 31 Pg. 12901)

BLM resurvey by Deborah M. Stephens and Harvey E. Wofford, surveyed April 1990 thru April 1995 under group #1521. (DCSO records Vol. 51 Page(s) 19599)

-----

Found - iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap properly mkd.

from which the remains of the original bearing trees

A cedar stump, 72 ins. diam., bears N. 54° E., 20 lks. dist., no marks visible.

A hemlock snag, size indeterminate, bears S. 6½° W., 15 lks. dist., no marks visible.

A hemlock snag, size indeterminate, bears N. 56° W., 35 lks. dist., with axe marks visible on partially healed blaze.

and the remains of a bearing tree mkd. by Tillman

A cedar snag, size indeterminate, bears N. 39 3/4° W., 181 lks. dist., with scribe marks S R11W S16 BT visible on decayed blaze. (Record, N. 33 3/4° W.)

and new bearing trees

An alder, 7 ins. diam., bears S. 88½° E., 64 lks. dist., mkd. T21S R11W S22 BT in the bark.

An alder, 15 ins. diam., bears N. 34½° W., 25 lks. dist., mkd. T21S R11W S16 BT in the bark.

Alongside the iron post is an iron rod, 3/8 in. diam., projecting 4 ft. above ground.