

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1214)

An Alder 9" dia.; which I marked ¼ S on W. face, for ¼ sec. cor., from which
 An Alder 8" dia., bears N.48°E., 22 lks. dist. mkd. ¼ S BT
 An Alder 7" dia., bears S.46¼°W., 19 lks. dist. mkd. ¼ S BT.

Survey by Richard J. Hintz - For: James Peck - March 9, 1977 - C.S. File 58/140-1

Set from the possible orig. BT:
 8" Alder BT, now 20", which bears N.48°E., 14.5 ft., axe marks but no scribe.
I Set a 3/4" I.P., from which
 A 32" Cedar bears N.20°E., 6.44 ft. mkd. ¼ S15 BT.

Eugene Wobbe - For: International Paper Co. - May 1987 (added 11/25/2015) - M104-43 A&B and C.S. File 63/59-1

Set - ¾"x4' alum rod with 3" alum. cap in place of ¾" pipe fd
New - 12" Alder S.55°W., 15.4'
 38" Cedar N.20°E., 6.44'
Affidavit concerning position of corner:
"To whom it may concern:
Regarding the ¼ corner between Sections 15 and 16, Township 21 South, Range 11 West, Willamette Meridian.
The pipe which suveyor Hintz set in 1977 for this corner is in the location that I have always remembered for the ¼ corner. I am a lifelong resident of this area and I have known this location for this corner since the early 1940's and it has been used by other surveyors as far back as that time.
James A. Peck"

BLM resurvey by Deborah M. Stephens and Harvey E. Wofford, surveyed April 1990 thru April 1995 under group #1521. (DCSO records Vol. 51 Page(s) 19616) (added full text 11/25/2015)

The ¼ sec. cor. of secs. 15 & 16, remonumented by Hintz in 1977, from original evidence no longer in existence, and perpetuated by Wobbe in 1987. Wobbe obtained an affidavit from James A. Peck, adjacent landowner, that verified the position of the corner perpetuated by Hintz, monumented with an aluminum rod, ¾" dia., flush with the ground surface, with aluminum cap mkd.

continued next page

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

IP TIMBERLAND OPERATING CO
RLS 1093
T21S ^{1/4} R11W
S 16 ^{1/4} S 15
1987
from which bearing trees mkd. by Hintz
A cedar, 42" dia. bears N.19½°E., 9½ lks with healed blaze
An alder, 10" dia., bears S. 57 1/4 W., 23 lks., with
scribe marks ¼ S16 BT visible in the bark.

Fd as per 1996 BLM survey by D Edwards 11/2015 - C.S. File
65/88-13