

PRIMARY CORNER DESCRIPTION Sec Cor for 3, 4, 9 and 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John W Meldrum, Deputy surveyor, under Contract #116, dated December 16, 1866 (DCSO records Vol. 3 Pg 1161)

-
- Set post for cor. to secs. 3, 4, 9 and 10, from which
- A Fir 24" dia., bears N.55°W., 47 lks. dist.
 - A Hemlock 6" dia., bears N.48°E., 33 lks. dist.
 - A Fir 30" dia., bears S.25°E., 18 lks. dist.
 - A Fir 26" dia., bears S.55°W., 30 lks. dist.

Douglas Co. Surveyors Office, MG, WS, MS - Sept. 1964 - C.S. 53/66-76

Corner searched for, Fd. ? - Not Fd. ?

Found 3/4" galv. iron pipe and 1 BT, A Fir snag, now 16" dia., S.25°E., 12 ft., old scribing found 'T21S R11W S10 BT'. Appears to be 70-75 yrs. old. Official govt. notes for this cor. is a duplication of notes for 33, 34, 3 and 4, (one mile North). Scribing faces I.P. found. No trace of scars or scribing can be found on any stumps of old trees in this area, except the one mentioned.

Douglas Co. Surveyors Office - James Byron, Deputy - John M. Powell and crew - June 29, 1967 - C.S. File 54/47 and M 33-18

Found - Unrecorded 3/4" I.P., 14" above ground, set from original BT.

Orig. now 16" Fir (called for 30") S.25°E., 11.9 ft. (face) Ring count is 80+ years on "BT" face, now snag, scribe marks visible "T21S R11W S10 BT" Depressions approx. where orig. SW and NE BTs should be.

DID NOT SET BRASS CAP.

New BTs -14" Spruce N.24°E., 37.5 ft. mkd. T21S R11W S3 CSBT
20" D.Fir S.23°E., 14.7 ft. mkd. T21S R11W S10 CSBT
28" Maple S.56°W., 42.6 ft. mkd. T21S R11W S9 CSBT.
52" D.Fir N.70°W., 24.5 ft. mkd. T21S R11W S4 CSBT.

Find stump called for in Forest Appraisal notes, now sawed open, bears S.86°W., 15.2 ft., 48" dia., no scribe found.

This corner lies on steep SW. slope approx. 150 ft. W. of top of spur ridge sloping South.

Douglas Co. Surveyors Office - L.E. Monrean; Peter L. Earle, crew - June 21, 1977 - C.S. file 59/34-42

Found - 3/4" I.P. 14" above ground, firmly set.
(Cont. Next Page)

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec Cor for 3, 4, 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Orig. BT, now 16" Fir (called for 30") bears S.25°E., 11.9 ft. Previously open blaze BT visible painted over.
No other orig. BTs found.
A 14" now 16" Spruce bears S.24°E., 38.9 ft. (Rec. 37.5 ft.) partially healed blaze "R11 S3 S B" visible.
A 20" now 26" D.Fir bears S.23°E., 17.7 ft. well healed blaze.
A 28" now 30" Maple bears S.56°W., 38.5 ft. (Rec. 42.6 ft.) partially healed blaze "21 R11 CS" visible.
A 52" now 60" D.Fir bears N.70°W., 24.5 ft. well healed blaze.
A stump 48" bears S.86°W., 15.2 ft. no scribe found.
Set 1" I.P. 30" long with brass cap attached mkd:
Douglas County Surveyor
T 21 S R 11 W
S 4 | S 3
S 9 | S 10
1977
Set 3/4" I.P. 49" long, along southerly edge of cap.