TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1215-16)

Set a post 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor. marked ¼ S. on N. face, from which

A Chittem, 9" dia., bears S.82°W., 110 lks. dist. mkd. ¼ S BT.

A Chittem 5" dia., bears N.61°E., 27 lks. dist. mkd. ¼ S BT.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #430, Surveyed June/Aug 1960 (DCSO records Vol. 31 Page(s) 12902)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼ S 15
S 22
T 21 S R 11 W
1960

from which

A Maple 38" dia., bears N.87°E., 45 lks. dist. mkd. ¼ S15 BT.

A Cedar 40" dia., bears S.23½°W., 270 lks. dist. mkd. ¼ S22 BT.

Fd. OK, May 1987 by E. Wobbe - M 104-43 A&B

Found and used in BLM resurvey by Deborah M. Stephens and Harvey E. Wofford, surveyed April 1990 thru April 1995 under group #1521. (DCSO records Vol. 51 Page(s) 19598)