

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 3 Page(s) 1183)

Set ¼ sec. cor. a post at foot of hills, from which
A Willow 8" dia., bears N.54½°E., 45 lks. dist.
An Alder 5" dia., bears S.28°W., 9 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1238-39)

¼ sec. cor. bet. secs. 34 and 35, which is a post, 4" sq., mkd. ¼ S on W. face, from which
An Alder 5" dia., bears S.28°W., 9 lks. dist. mkd. ¼ S BT
An Alder 16" dia., bears N.36°W., 40 lks. dist. mkd. ¼ S BT.
This latter bearing tree in place of the former willow, which has fallen down.

H.T. Lewis, Eng. #722 - May 9, 1939 - C.S. File 16/55 and ("old" corner book Vol 1 Pg 15)

At the ¼ corner between sections 34 and 35, I found the scribe on the original Alder, BT had been rotted out, but in the soft muck where the post was supposed to set, I found the well preserved point of an old wooden stake, also, running N. from this point, is a well blazed line, whose topography checks for a considerable distance with the govt. field notes. I therefore Set an 1½" galv. pipe 4 ft. long, from which
A forked Spruce 28" dia., bears S.10°E., 5 ft. mkd. "¼ S T21S R11W S35 BT 722".
A Spruce 36" dia., bears S.75°W., 24 ft. mkd. "¼ S T21S R11W S34 BT 722".

Survey by James W. Prochnau, PLS #1305 - For: U.S. Forest Service - Feb. 1984 - C.S. File 58/294 and M 96-65 A & B

Found - 47" forked Spruce bears S.10°E., 5.0 ft. healed face.
43" Spruce bears S.75°W., 24.0 ft. healed face.
Set Witness corner, 3" alum. cap on 2½" x 30" alum. pipe bears N.4°03'44"W., 30.0 ft. from true corner. Cap stamped per BLM manual and with PLS 1305.
New BT - 6" Alder bears S.56°E., 10.6 ft. bark scribed "X BT".

(Cont. Next Page)

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set reference monument, 3" alum. cap on 2½" x 30"
alum. pipe bears N.71°30'24"W., 50.82 ft. from
W.C. marked RM W.C. S34 S35 1984 PLS 50.82 ft.
(with arrow point to corner)