

PRIMARY CORNER DESCRIPTION W.P. bet. Secs. 26 and 27

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1210-11)</p> <p>-----</p> <p>(10.70 chs. S. of sec. cor.) A barberry 8" dia., which I marked S26 on E. and S27 on W. side, from which A Fir 42' dia., bears N.29°E., 47 lks. dist. mkd. S26 BT An Alder 12" dia., bears S.88°W., 15 lks. dist. mkd. S27 BT.</p>
<p>BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #430, Surveyed June/Aug 1960 (DCSO records Vol. 31 Page(s) 12892)</p> <p>-----</p> <p>A witness point between secs. 26 and 27, bears S.0°01'E., 9.21 chs. dist., determined at record bearing and distance from the only remaining original bearing tree: A sawed Fir stump 52" dia., 14 ft. high, bears N.29°E., 47 lks. dist., with scribe marks S26 BT visible on bark. At the point for the witness point, which falls in a dirt access road, 15 lks. wide, bearing E. and W. Set an iron pipe 16" long, 1" dia., 28" in the road, for a perpetuation of the witness point.</p>
<p>Survey by James W. Prochnau - For: U.S. Forest Service - Feb. 24, 1984 - M 96-62; C.S. File 58/294 and M 96-61 A&B</p> <p>-----</p> <p>Found - Orig. BT, 62" D.Fir high stump bears N.29°E., 31.02 ft., visible scribe. Set 3" alum. cap on 2½" x 30" alum. pipe. Rock mound. New BTs -10" Alder bears N.77°E., 42.8 ft. bark scribed X BT. 5" Maple bears N.21°W., 49.3 ft. scribed X BT.</p>
<p> </p>